

-- Start of DDL Script for Table ISPDEV.CG_REF_CODES
-- Generated 22-Apr-2009 15:31:38 from ISPDEV@photop

```
CREATE TABLE ispdev.cg_ref_codes
  (code_domain          VARCHAR2(100),
   code                 VARCHAR2(240),
   descr               VARCHAR2(240))
PCTFREE      10
INITTRANS    1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- Indexes for ISPDEV.CG_REF_CODES

```
CREATE UNIQUE INDEX ispdev.crc_primary_key_i ON ispdev.cg_ref_codes
  (
   code                 ASC,
   code_domain         ASC
  )
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
NOLOGGING
/
```

```
CREATE INDEX ispdev.x_cg_ref_codes_1 ON ispdev.cg_ref_codes
  (
   code_domain         ASC,
   code                ASC
  )
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- End of DDL script for Table ISPDEV.CG_REF_CODES

-- Start of DDL Script for Table ISPDEV.COUNTIES
-- Generated 22-Apr-2009 15:31:38 from ISPDEV@photop

Photo Radar Schema ISPDEV_ddl.sql

```
CREATE TABLE ispdev.counties
  (name          VARCHAR2(20) NOT NULL,
   county_seat  VARCHAR2(40),
   code_alpha   VARCHAR2(4),
   county       CHAR(3) NOT NULL,
   ori          CHAR(9))
PCTFREE        10
INITTRANS      1
MAXTRANS       255
TABLESPACE     ispdev_data
STORAGE        (
  INITIAL       1048576
  MINEXTENTS   1
  MAXEXTENTS   2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.COUNTIES

-- Start of DDL Script for Table ISPDEV.EXCEPTIONS
-- Generated 22-Apr-2009 15:31:38 from ISPDEV@photop

```
CREATE TABLE ispdev.exceptions
  (row_id        ROWID,
   owner         VARCHAR2(30),
   table_name    VARCHAR2(30),
   constraint    VARCHAR2(30))
PCTFREE        10
INITTRANS      1
MAXTRANS       255
TABLESPACE     ispdev_data
STORAGE        (
  INITIAL       65536
  MINEXTENTS   1
  MAXEXTENTS   2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.EXCEPTIONS

-- Start of DDL Script for Table ISPDEV.TBLACCIDENTTYPE
-- Generated 22-Apr-2009 15:31:38 from ISPDEV@photop

```
CREATE TABLE ispdev.tblaccidenttype
  (iaccidenttypeid NUMBER NOT NULL,
   vcaccidenttypedescription VARCHAR2(100),
   dupdateddate    DATE,
   iupdatedby      NUMBER)
PCTFREE        10
INITTRANS      1
MAXTRANS       255
TABLESPACE     ispdev_data
STORAGE        (
  INITIAL       1048576
```

```

MINEXTENTS 1
MAXEXTENTS 2147483645

```

```

/ )

```

```
-- Constraints for ISPDEV.TBLACCIDENTTYPE
```

```

ALTER TABLE ispdev.tblaccidenttype
ADD CONSTRAINT pk_accidentid PRIMARY KEY (iaccidenttypeid)
USING INDEX
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE (
  INITIAL     65536
  MINEXTENTS 1
  MAXEXTENTS 2147483645
)

```

```

/ )

```

```
-- End of DDL Script for Table ISPDEV.TBLACCIDENTTYPE
```

```
-- Start of DDL Script for Table ISPDEV.TBLBOND
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop
```

```

CREATE TABLE ispdev.tblbond
  (ibondidid                NUMBER NOT NULL,
  ccitationnumber           VARCHAR2(10),
  idefendantbonddepositamount NUMBER,
  vcbondcardno              VARCHAR2(20),
  cbondcompanyname          CHAR(3),
  idefendantbondreceiptnumber NUMBER,
  ibondpostedonotherticket  NUMBER,
  vcconfinementlocationforbond VARCHAR2(40),
  cdefendantbondtype1       CHAR(2),
  ndefendantbondamount      NUMBER,
  dudateddate               DATE,
  iupdatedby                NUMBER)
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE (
  INITIAL     1048576
  MINEXTENTS 1
  MAXEXTENTS 2147483645
)

```

```

/ )

```

```
-- Constraints for ISPDEV.TBLBOND
```

```

ALTER TABLE ispdev.tblbond
ADD CONSTRAINT pk_bondid PRIMARY KEY (ibondidid)

```

```

USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE      (
    INITIAL     65536
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/

```

```
-- End of DDL Script for Table ISPDEV.TBLBOND
```

```
-- Start of DDL Script for Table ISPDEV.TBLCATEGORY
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop
```

```

CREATE TABLE ispdev.tblcategory
  (icategoryid          NUMBER NOT NULL,
  vccategorydescription VARCHAR2(100),
  dupdateddate         DATE,
  iupdatedby           NUMBER)
  PCTFREE      10
  INITTRANS    1
  MAXTRANS     255
  TABLESPACE  ispdev_data
  STORAGE      (
    INITIAL     1048576
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/

```

```
-- Constraints for ISPDEV.TBLCATEGORY
```

```

ALTER TABLE ispdev.tblcategory
ADD CONSTRAINT pk_categoryid PRIMARY KEY (icategoryid)
USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE      (
    INITIAL     65536
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/

```

```
-- End of DDL Script for Table ISPDEV.TBLCATEGORY
```

```
-- Start of DDL Script for Table ISPDEV.TBLCHARGESTATUTECITATIONTYPES
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop
```

```

CREATE TABLE ispdev.tblchargestatutecitationtypes
  (ichargestatutecitationtypeid NUMBER NOT NULL,
  vcdescription                 VARCHAR2(255),
  )

```

```

        dupdateddate          DATE,
        iupdatedby           NUMBER)
    PCTFREE          10
    INITRANS         1
    MAXTRANS         255
    TABLESPACE      ispdev_data
    STORAGE (
        INITIAL      1048576
        MINEXTENTS   1
        MAXEXTENTS   2147483645
    )
/

```

-- Constraints for ISPDEV.TBLCHARGESTATUTECITATIONTYPES

```

ALTER TABLE ispdev.tblchargestatutecitationtypes
ADD CONSTRAINT pk_chargestatutecitationid PRIMARY KEY (
    ichargestatutecitationtypeid)
USING INDEX
    PCTFREE          10
    INITRANS         2
    MAXTRANS         255
    TABLESPACE      ispdev_index
    STORAGE (
        INITIAL      65536
        MINEXTENTS   1
        MAXEXTENTS   2147483645
    )
/

```

-- End of DDL Script for Table ISPDEV.TBLCHARGESTATUTECITATIONTYPES

-- Start of DDL Script for Table ISPDEV.TBLCOMMERCIALMOTORVEHICLEOWNER
 -- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

```

CREATE TABLE ispdev.tblcommercialmotorvehicleowner
    (vccarriename          VARCHAR2(60),
    vccarrieraddress1     VARCHAR2(20),
    vccarrieraddress2     VARCHAR2(20),
    vccarriercity         VARCHAR2(20),
    vccarrierstate        VARCHAR2(2),
    vccarrierzip          VARCHAR2(5),
    vccarrierzipsuffix    VARCHAR2(4),
    dupdateddate          DATE,
    iupdatedby           NUMBER)
    PCTFREE          10
    INITRANS         1
    MAXTRANS         255
    TABLESPACE      ispdev_data
    STORAGE (
        INITIAL      1048576
        MINEXTENTS   1
        MAXEXTENTS   2147483645
    )
/

```

Photo Radar Schema ISPDEV_ddl.sql

-- End of DDL Script for Table ISPDEV.TBLCOMMERCIALMOTORVEHICLEOWNER

-- Start of DDL Script for Table ISPDEV.TBLCOMMERCIALVEHICLEBOND

-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

```
CREATE TABLE ispdev.tblcommercialvehiclebond
  (ioverweightfine          NUMBER,
  ioverweightclerkfee      NUMBER,
  ioverweightcourtautomation NUMBER,
  ioverweightdocumentstorage NUMBER,
  ioverweightcourtfund     NUMBER,
  ioverweightsurcharge     NUMBER,
  ioverweightotherfee      NUMBER,
  dupdatedate              DATE,
  iupdatatedby             NUMBER)
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE     (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLCOMMERCIALVEHICLEBOND

-- Start of DDL Script for Table ISPDEV.TBLCOMMERCIALVEHICLEVIOLATION

-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

```
CREATE TABLE ispdev.tblcommercialvehicleviolation
  (caxlegrossbridgeindicator CHAR(1),
  iroadsurfaceweight         NUMBER,
  iaxles                      NUMBER,
  iaxleweightinexcess       NUMBER,
  iaxleweight                NUMBER,
  ipoundsinexcess           NUMBER,
  vcaxlepermitnumber        VARCHAR2(7),
  vcgrosspermitnumber       VARCHAR2(7),
  igrossweight              NUMBER,
  cilcsindicator            CHAR(1))
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE     (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- Constraints for ISPDEV.TBLCOMMERCIALVEHICLEVIOLATION

```
ALTER TABLE ispdev.tblcommercialvehicleviolation
ADD CONSTRAINT chk_commaxgrbrind CHECK (CAXLEGROSSBRIDGEINDICATOR IN ('A', 'G',
'B'))
/
```

```
ALTER TABLE ispdev.tblcommercialvehicleviolation
ADD CONSTRAINT chk_axles CHECK (IAXLES IN (0, 1, 2, 3, 4, 5, 6))
/
```

```
ALTER TABLE ispdev.tblcommercialvehicleviolation
ADD CONSTRAINT chk_commilcsindicator CHECK (CILCSINDICATOR IN ('3', '4'))
/
```

-- End of DDL Script for Table ISPDEV.TBLCOMMERCIALVEHICLEVIOLATION

-- Start of DDL Script for Table ISPDEV.TBLCOURT
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

```
CREATE TABLE ispdev.tbtcourt
(
    icourtid                NUMBER NOT NULL,
    icourthistoricid        NUMBER,
    vcname                  VARCHAR2(60),
    vcphone                 NUMBER,
    vcaddress1              VARCHAR2(40),
    vcaddress2              VARCHAR2(40),
    vcaddress3              VARCHAR2(40),
    vcaddress4              VARCHAR2(40),
    vccity                  CHAR(40),
    vcziporpostalcode       VARCHAR2(10),
    vcstate                 CHAR(2),
    dcreationdate           DATE,
    vccreatedby             VARCHAR2(30),
    deffectivedate          DATE,
    vccourtcode             VARCHAR2(20),
    vccourtdumpheader       VARCHAR2(30),
    ccourtappearreq        CHAR(1),
    iappearancedays        NUMBER,
    ipenalty                NUMBER,
    ijurisdictionhistoricid NUMBER,
    dcircuitcourtdate       DATE,
    dcircuitcourtttime     NUMBER,
    campindicator           CHAR(2),
    dupdateddate            DATE,
    iupdatedby             NUMBER)
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
    INITIAL      1048576
    MINEXTENTS  1
    MAXEXTENTS  2147483645
)
/
```

-- Constraints for ISPDEV.TBLCOURT

Photo Radar Schema ISPDEV_ddl.sql

```
ALTER TABLE ispdev.tblcourt
ADD CONSTRAINT pk_courtid PRIMARY KEY (icourtid)
USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      65536
    MINEXTENTS   1
    MAXEXTENTS  2147483645
  )
/
```

-- Triggers for ISPDEV.TBLCOURT

```
CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_INS_tblCourt
AFTER INSERT ON tblCourt
FOR EACH ROW
BEGIN
-- Inserting selected records into tblSyncAudit (Audit table)
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblCourt',
   'iCourtId',
   :new.icourtid,
   'iCourtId',
   :new.icourtid,
   'I',
   USER,
   sysdate,
   null);

INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblCourt',
   'iCourtId',
   :new.icourtid,
```

```
'iCourthistoricId',
:new.icourthistoricid,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcName',
:new.vcname,
'I',
USER,
sysdate,
null);
```

```
/*INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcPhone',
:new.vcphone,
'I',
USER,
sysdate,
null);*/
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
```

```
        bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'vcAddress1',
     :new.vcaddress1,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblsyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'vcAddress2',
     :new.vcaddress2,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblsyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'vcAddress3',
     :new.vcaddress3,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblsyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
```

```

vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcAddress4',
:new.vcaddress4,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcCity',
:new.vccity,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcZipOrPostalCode',
:new.vcziporpostalcode,
'I',
USER,
sysdate,

```

```
    null);
```

```
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'vcState',
     :new.vcstate,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'dCreationDate',
     :new.dcreationdate,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
```

```

:new.icourtId,
'vcCreatedBy',
:new.vccreatedby,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'dEffectiveDate',
:new.deffectivedate,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcCourtCode',
:new.vccourtcode,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,

```

```

vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'vcCourtDumpHeader',
:new.vccourtdumpheader,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'cCourtAppearReq',
:new.ccourtappearreq,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'appearanceDays',
:new.iappearancedays,
'I',
USER,
sysdate,
null);

```

```

-----
INSERT INTO tblSyncAudit
(iauditId,
vcAuditTableName,

```

```
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'ipenalty',
:new.ipenalty,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'ijurisdictionHistoricId',
:new.ijurisdictionHistoricId,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtId',
:new.icourtId,
'dCircuitCourtDate',
:new.dCircuitCourtDate,
'I',
USER,
sysdate,
```

```
    null);
```

```
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'dCircuitCourtTime',
     :new.dccircuitcourttime,
     'I',
     USER,
     sysdate,
     null);
```

```
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblCourt',
     'iCourtId',
     :new.icourtid,
     'CAMPIndicator',
     :new.campindicator,
     'I',
     USER,
     sysdate,
     null);
```

```
END TRG_SYNCAUDIT_INS_tblCourt;
/
```

```
CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_tblCourt
AFTER UPDATE ON tblCourt
FOR EACH ROW
BEGIN
IF (:old.icourtid<>:new.icourtid) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
```

```

vcAuditColumnOldValue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtid',
:old.icourtid,
'icourtid',
:old.icourtid,
:new.icourtid,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.Icourthistoricid<>:new.Icourthistoricid) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnOldValue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtid',
:old.icourtid,
'Icourthistoricid',
:old.Icourthistoricid,
:new.Icourthistoricid,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcaddress1<>:new.vcaddress1) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnOldValue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',

```

```

'icourtid',
:old.icourtid,
'vcaddress1',
:old.vcaddress1,
:new.vcaddress1,
'U',
USER,
sysdate,
null);
END IF;

```

```

IF (:old.vcaddress2<>:new.vcaddress2) THEN
INSERT INTO tblsyncAudit

```

```

(iauditid,
vCAuditTableName,
vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,
vCAuditColumnOldValue,
vCAuditColumnNewValue,
vCAuditColumnAction,
vCAuditUpdatedBy,
vCAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtid',
:old.icourtid,
'vcaddress2',
:old.vcaddress2,
:new.vcaddress2,
'U',
USER,
sysdate,
null);
END IF;

```

```

IF (:old.vccity<>:new.vccity) THEN
INSERT INTO tblsyncAudit

```

```

(iauditid,
vCAuditTableName,
vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,
vCAuditColumnOldValue,
vCAuditColumnNewValue,
vCAuditColumnAction,
vCAuditUpdatedBy,
vCAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtid',
:old.icourtid,
'vccity',
:old.vccity,
:new.vccity,
'U',
USER,
sysdate,
null);

```

```
END IF;
```

```
IF (:old.vcstate<>:new.vcstate) THEN
INSERT INTO tblSyncAudit
```

```
(iauditid,
  vCAuditTableName,
  vCAuditTableIDKeyColumn,
  vCAuditTableIDKeyValue,
  vCAuditColumnName,
  vCAuditColumnOldValue,
  vCAuditColumnNewValue,
  vCAuditColumnAction,
  vCAuditUpdatedBy,
  vCAuditUpdatedDate,
  bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
  'tblCourt',
  'icourtid',
  :old.icourtid,
  'vcstate',
  :old.vcstate,
  :new.vcstate,
  'U',
  USER,
  sysdate,
  null);
```

```
END IF;
```

```
IF (:old.vcziporpostalcode<>:new.vcziporpostalcode) THEN
INSERT INTO tblSyncAudit
```

```
(iauditid,
  vCAuditTableName,
  vCAuditTableIDKeyColumn,
  vCAuditTableIDKeyValue,
  vCAuditColumnName,
  vCAuditColumnOldValue,
  vCAuditColumnNewValue,
  vCAuditColumnAction,
  vCAuditUpdatedBy,
  vCAuditUpdatedDate,
  bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
  'tblCourt',
  'icourtid',
  :old.icourtid,
  'vcziporpostalcode',
  :old.vcziporpostalcode,
  :new.vcziporpostalcode,
  'U',
  USER,
  sysdate,
  null);
```

```
END IF;
```

```
/*IF (:old.vcphone<>:new.vcphone) THEN
INSERT INTO tblSyncAudit
```

```
(iauditid,
  vCAuditTableName,
  vCAuditTableIDKeyColumn,
  vCAuditTableIDKeyValue,
  vCAuditColumnName,
```

```

vcAuditColumnOldValue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblCourt',
'icourtid',
:old.icourtid,
'vcphone',
:old.vcphone,
:new.vcphone,
'U',
USER,
sysdate,
null);
END IF;*/
END TRG_SYNCAUDIT_UPD_tblCourt;
/

-- End of DDL Script for Table ISPDEV.TBLCOURT

-- Foreign Key
ALTER TABLE ispdev.tblcourt
ADD CONSTRAINT fk_jurisdictionid FOREIGN KEY (ijurisdictionhistoricid)
REFERENCES ISPDEV.tbljurisdiction (ijurisdictionhistoricid)
DISABLE NOVALIDATE
/
-- End of DDL script for Foreign Key(s)
-- Start of DDL Script for Table ISPDEV.TBLDISPOSITION
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

CREATE TABLE ispdev.tbldisposition
(idispositionid          NUMBER NOT NULL,
ccitationnumber         VARCHAR2(10),
cdefendantplea          CHAR(1),
ctrial                  CHAR(1),
cfinding                CHAR(3),
dcourtactiondate        DATE,
cfineamount             NUMBER,
cinstitution            CHAR(1),
camended                CHAR(1),
vcamendedoffense        CHAR(8),
camendedplea            CHAR(1),
camendedtrial           CHAR(1),
camendedfinding         CHAR(3),
vcdocketnumber          VARCHAR2(12),
dcourtfileddate         DATE,
vcnextticketnumber      VARCHAR2(7),
icaseyear                VARCHAR2(4),
ccasetypecode           CHAR(2),
icasesequencenumber     VARCHAR2(8),
vccircuitcourtncciccode VARCHAR2(9),
icookcountydistrictcode VARCHAR2(1),
dcaseinitiationdate     DATE,
cchargestatuscode       CHAR(1),
cchargelevelofgovt     CHAR(1),
ichargeoffensecode      VARCHAR2(7),
vcarrestagencyniccode  VARCHAR2(9),
coverweightindicator    CHAR(1),

```

Photo Radar Schema ISPDEV_ddl.sql

```

vctrafficticketnumber      VARCHAR2(8),
ichargedisposition         VARCHAR2(3),
ichargedispositiontype     VARCHAR2(1),
dchargedispositiondate     DATE,
cchargedispositionindicator CHAR(1),
dsentencedate              DATE,
isentencetype              VARCHAR2(3),
ccounty                    CHAR(3),
dupdateddate               DATE,
iupdatedby                 NUMBER,
idispositionmicrofilmnumber NUMBER,
dfileprocessdate           DATE DEFAULT SYSDATE NOT NULL)
PCTFREE      10
INITTRANS    1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL     1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- Indexes for ISPDEV.TBLDISPOSITION

```

CREATE UNIQUE INDEX ispdev.tbldisposition_uk ON ispdev.tbldisposition
(
  ccitationnumber          ASC,
  ichargeoffensecode       ASC,
  ichargedisposition       ASC,
  dchargedispositiondate   ASC,
  cchargestatuscode        ASC,
  vcamendedoffense         ASC,
  camendedfinding          ASC
)
PCTFREE      10
INITTRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     65536
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- Constraints for ISPDEV.TBLDISPOSITION

```

ALTER TABLE ispdev.tbldisposition
ADD CONSTRAINT pk_dispositionid PRIMARY KEY (idispositionid)
USING INDEX
PCTFREE      10
INITTRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     131072

```

Photo Radar Schema ISPDEV_ddl.sql

```
MINEXTENTS 1
MAXEXTENTS 2147483645
```

```
/ )
```

-- Triggers for ISPDEV.TBLDISPOSITION

```
CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_INS_Disposition
AFTER INSERT ON tblDisposition
FOR EACH ROW
BEGIN
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
```

```
vcAuditColumnName,vCAuditColumnNewValue,
vcAuditColumnAction,vCAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'cCitationNumber', :new.ccitationnumber,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
```

```
vcAuditColumnName,vCAuditColumnNewValue,
vcAuditColumnAction,vCAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'DCHARGEDISPOSITIONDATE', :new.DCHARGEDISPOSITIONDATE,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
```

```
vcAuditColumnName,vCAuditColumnNewValue,
vcAuditColumnAction,vCAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'DCOURTACTIONDATE', :new.DCOURTACTIONDATE,
'I',USER, sysdate, null);
```

```
IF (:new.CDEFENDANTPLEA<>null) THEN
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
```

```
vcAuditColumnName,vCAuditColumnNewValue,
vcAuditColumnAction,vCAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'CDEFENDANTPLEA', :new.CDEFENDANTPLEA,
'I',USER, sysdate, null);
```

```
end if;
```

```
IF (:new.CTRIAL<>null) THEN
```

Photo Radar Schema ISPDEV_ddl.sql

```

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
                        'CTRIAL', :new.CTRIAL,
                        'I',USER, sysdate, null);
                        end if;
IF (:new.CFINDING<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
                        'CFINDING', :new.CFINDING,
                        'I',USER, sysdate, null);

                        end if;
IF (:new.CFINEAMOUNT<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
                        'CFINEAMOUNT', :new.CFINEAMOUNT,
                        'I',USER, sysdate, null);
                        end if;
IF (:new.CINSTITUTION<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
                        'CINSTITUTION', :new.CINSTITUTION,
                        'I',USER, sysdate, null);
                        end if;
IF (:new.CAMENDED<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
                        'CAMENDED', :new.CAMENDED,

```

Photo Radar Schema ISPDEV_ddl.sql

```
'I',USER, sysdate, null);
        end if;
IF (:new.VCAMENDEDOFFENSE<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'VCAMENDEDOFFENSE', :new.VCAMENDEDOFFENSE,
        'I',USER, sysdate, null);
        end if;
IF (:new.CAMENDEDPLEA<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'CAMENDEDPLEA', :new.CAMENDEDPLEA,
        'I',USER, sysdate, null);
        end if;
IF (:new.CAMENDEDTRIAL<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'CAMENDEDTRIAL', :new.CAMENDEDTRIAL,
        'I',USER, sysdate, null);
        end if;
IF (:new.CAMENDEDFINDING<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'CAMENDEDFINDING', :new.CAMENDEDFINDING,
        'I',USER, sysdate, null);
        end if;
IF (:new.VCDOCKETNUMBER<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'CAMENDEDFINDING', :new.CAMENDEDFINDING,
        'I',USER, sysdate, null);
        end if;
IF (:new.VCDOCKETNUMBER<>null) THEN
    INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
        vcAuditColumnName,vcAuditColumnNewValue,
        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
        ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
        'CAMENDEDFINDING', :new.CAMENDEDFINDING,
        'I',USER, sysdate, null);
        end if;
```

Photo Radar Schema ISPDEV_ddl.sql

```
VALUES
    ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'VCDOCKETNUMBER', :new.VCDOCKETNUMBER,
'I',USER, sysdate, null);
    end if;
IF (:new.DCOURTFILEDDATE<>null) THEN

INSERT INTO tblSyncaudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'DCOURTFILEDDATE', :new.DCOURTFILEDDATE,
'I',USER, sysdate, null);
    end if;
IF (:new.IDISPOSITIONMICROFILMNUMBER<>null) THEN

INSERT INTO tblSyncaudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblDisposition',
'cCitationNumber',:new.cCitationNumber,
'IDISPOSITIONMICROFILMNUMBER',
:new.IDISPOSITIONMICROFILMNUMBER,
'I',USER, sysdate, null);
    end if;

END TRG_SYNCAUDIT_INS_Disposition;
/

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_Disposition
AFTER UPDATE ON tblDisposition
FOR EACH ROW
BEGIN
IF (:old.ccitationnumber<>:new.ccitationnumber) THEN
INSERT INTO tblSyncaudit
    (iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
'tblDisposition',
```

Photo Radar Schema ISPDEV_ddl.sql

```

        'cCitationNumber',
        :old.cCitationNumber,
        'cCitationNumber',
        :old.ccitationnumber,
        :new.ccitationnumber,
        'U',
        USER,
        sysdate,
        null);
END IF;

```

```

IF (:old.DCHARGEDISPOSITIONDATE<>:new.DCHARGEDISPOSITIONDATE) THEN
INSERT INTO tblsyncAudit

```

```

    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDisposition',
     'cCitationNumber',
     :old.cCitationNumber,
     'DCHARGEDISPOSITIONDATE',
     :old.DCHARGEDISPOSITIONDATE,
     :new.DCHARGEDISPOSITIONDATE,
     'U',
     USER,
     sysdate,
     null);
END IF;

```

```

IF (:old.DCOURTACTIONDATE<>:new.DCOURTACTIONDATE) THEN
INSERT INTO tblsyncAudit

```

```

    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDisposition',
     'cCitationNumber',
     :old.cCitationNumber,
     'DCOURTACTIONDATE',
     :old.DCOURTACTIONDATE,
     :new.DCOURTACTIONDATE,
     'U',
     USER,
     sysdate,
     null);

```

```

END IF;
IF (:old.CDEFENDANTPLEA<>:new.CDEFENDANTPLEA) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDisposition',
     'cCitationNumber',
     :old.cCitationNumber,
     'CDEFENDANTPLEA',
     :old.CDEFENDANTPLEA,
     :new.CDEFENDANTPLEA,
     'U',
     USER,
     sysdate,
     null);
END IF;

```

```

IF (:old.CTRIAL<>:new.CTRIAL) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDisposition',
     'cCitationNumber',
     :old.cCitationNumber,
     'CTRIAL',
     :old.CTRIAL,
     :new.CTRIAL,
     'U',
     USER,
     sysdate,
     null);
END IF;

```

```

IF (:old.CFINDING<>:new.CFINDING) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,

```

```

vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'CFINDING',
:old.CFINDING,
:new.CFINDING,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.CFINEAMOUNT<>:new.CFINEAMOUNT) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'CFINEAMOUNT',
:old.CFINEAMOUNT,
:new.CFINEAMOUNT,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.CINSTITUTION<>:new.CINSTITUTION) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',

```

```

:old.cCitationNumber,
'CINSTITUTION',
:old.CINSTITUTION,
:new.CINSTITUTION,
'U',
USER,
sysdate,
null);
END IF;

```

```
IF (:old.CAMENDED<>:new.CAMENDED) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'CAMENDED',
:old.CAMENDED,
:new.CAMENDED,
'U',
USER,
sysdate,
null);
END IF;
```

```
IF (:old.VCAMENDEDOFFENSE<>:new.VCAMENDEDOFFENSE) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'VCAMENDEDOFFENSE',
:old.VCAMENDEDOFFENSE,
:new.VCAMENDEDOFFENSE,
'U',
USER,
sysdate,
null);
END IF;
```

Photo Radar Schema ISPDEV_ddl.sql

```
IF (:old.CAMENDEDPLEA<>:new.CAMENDEDPLEA) THEN
```

```
INSERT INTO tblSyncAudit
```

```
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
Vcauditcolumnoldvalue,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,  
'tblDisposition',  
'cCitationNumber',  
:old.cCitationNumber,  
'CAMENDEDPLEA',  
:old.CAMENDEDPLEA,  
:new.CAMENDEDPLEA,  
'U',  
USER,  
sysdate,  
null);
```

```
END IF;
```

```
IF (:old.CAMENDEDTRIAL<>:new.CAMENDEDTRIAL) THEN
```

```
INSERT INTO tblSyncAudit
```

```
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
Vcauditcolumnoldvalue,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,  
'tblDisposition',  
'cCitationNumber',  
:old.cCitationNumber,  
'CAMENDEDTRIAL',  
:old.CAMENDEDTRIAL,  
:new.CAMENDEDTRIAL,  
'U',  
USER,  
sysdate,  
null);
```

```
END IF;
```

```
IF (:old.CAMENDEDFINDING<>:new.CAMENDEDFINDING) THEN
```

```
INSERT INTO tblSyncAudit
```

```
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
Vcauditcolumnoldvalue,
```

```

vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'CAMENDEDFINDING',
:old.CAMENDEDFINDING,
:new.CAMENDEDFINDING,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.VCDOCKETNUMBER<>:new.VCDOCKETNUMBER) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',
:old.cCitationNumber,
'VCDOCKETNUMBER',
:old.VCDOCKETNUMBER,
:new.VCDOCKETNUMBER,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.DCOURTFILEDDATE<>:new.DCOURTFILEDDATE) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDisposition',
'cCitationNumber',

```

Photo Radar Schema ISPDEV_ddl.sql

```

:old.cCitationNumber,
'DCOURTFILEDDATE',
:old.DCOURTFILEDDATE,
:new.DCOURTFILEDDATE,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.IDISPOSITIONMICROFILMNUMBER<>:new.IDISPOSITIONMICROFILMNUMBER) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   Vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblDisposition',
   'cCitationNumber',
   :old.cCitationNumber,
   'IDISPOSITIONMICROFILMNUMBER',
   :old.IDISPOSITIONMICROFILMNUMBER,
   :new.IDISPOSITIONMICROFILMNUMBER,
   'U',
   USER,
   sysdate,
   null);
END IF;
END TRG_SYNCAUDIT_UPD_Disposition;
/

CREATE OR REPLACE TRIGGER ISPDEV.TBLDISP_B_U
  BEFORE
  UPDATE
  ON TBLDISPOSITION
  REFERENCING OLD AS OLD NEW AS NEW
  FOR EACH ROW
BEGIN
  If updating then
    :new.dfileprocessdate := sysdate;
  end if;
end;
/

-- End of DDL Script for Table ISPDEV.TBLDISPOSITION

-- Foreign Key
ALTER TABLE ispdev.tblDisposition
ADD CONSTRAINT fk_disposition_userid FOREIGN KEY (iupdatedby)
REFERENCES ISPDEV.tblusers (iuserid)
/
ALTER TABLE ispdev.tblDisposition
ADD CONSTRAINT fk_ccitationnumber FOREIGN KEY (ccitationnumber)
REFERENCES ISPDEV.tblviolation (ccitationnumber)

```

```

/
-- End of DDL script for Foreign Key(s)
-- Start of DDL Script for Table ISPDEV.TBLDRIVER
-- Generated 22-Apr-2009 15:31:39 from ISPDEV@photop

CREATE TABLE ispdev.tbldriver
    (ccitationnumber          VARCHAR2(10),
    vcfirstname              VARCHAR2(14),
    vcmiddlename             VARCHAR2(14),
    vclastname               VARCHAR2(14),
    vcnamesuffix            VARCHAR2(3),
    vcaddress1               VARCHAR2(20),
    vcaddress2              VARCHAR2(20),
    vccity                   VARCHAR2(25),
    cstateorprovince        CHAR(2),
    vcziporpostalcode       VARCHAR2(9),
    vcdriverlicenseno       VARCHAR2(25),
    cdriverlicensestate     CHAR(2),
    itelephoneno            NUMBER,
    ddateofbirth            DATE,
    cgender                  CHAR(1),
    ceyecolor                CHAR(3),
    chaircolor               CHAR(3),
    cweight                  CHAR(3),
    cheight                  CHAR(3),
    crace                    CHAR(1),
    clicenseclass            CHAR(3),
    dlicissue                VARCHAR2(8),
    dlicexpire              VARCHAR2(8),
    vcstateidnumber         VARCHAR2(8),
    cmunicipality            CHAR(5),
    cscalenum               CHAR(4),
    ccommercialdriverlicholder CHAR(1),
    dupdateddate            DATE,
    iupdatedby              NUMBER,
    vcresidencezip          VARCHAR2(5),
    vcresidencezipsuffix    VARCHAR2(4))
PCTFREE          10
INITRANS        1
MAXTRANS        255
TABLESPACE      ispdev_data
STORAGE (
    INITIAL      2097152
    MINEXTENTS  1
    MAXEXTENTS  2147483645
)
/

-- Constraints for ISPDEV.TBLDRIVER

ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_licenceclass CHECK (Clicenseclass IN ('A','B','C','D','L','M'))
DISABLE NOVALIDATE
/

ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_cdholder CHECK (CCOMMERCIALDRIVERLICHOLDER IN ('Y','N','U'))
/

```

Photo Radar Schema ISPDEV_ddl.sql

```
ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_cggender CHECK (CGENDER IN ('M','F','U'))
DISABLE NOVALIDATE
/
```

```
ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_ceyecolor CHECK (CEYECOLOR IN ('BLK','GRY','BLU', 'GRN', 'BRO',
'HAZ', 'MAR', 'PNK'))
DISABLE NOVALIDATE
/
```

```
ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_chaircolor CHECK (CHAIRCOLOR IN ('BAL','BLK','BLN', 'BLU', 'BRO',
'GRN', 'GRY', 'ONG', 'PLE', 'RED', 'SDY', 'WHI', 'XXX'))
DISABLE NOVALIDATE
/
```

```
ALTER TABLE ispdev.tbldriver
ADD CONSTRAINT chk_crace CHECK (CRACE IN ('W','B','H', 'A', 'I'))
DISABLE NOVALIDATE
/
```

-- Triggers for ISPDEV.TBLDRIVER

```
CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_UPD_tblDriver
AFTER UPDATE ON tblDriver
FOR EACH ROW
BEGIN
IF (:old.ccitationnumber<>:new.ccitationnumber) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'cCitationNumber',
:old.ccitationnumber,
:new.ccitationnumber,
'U',
USER,
sysdate,
null);
END IF;
```

```
IF (:old.vcfirstname<>:new.vcfirstname) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
```

```

vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'vcfirstname',
:old.vcfirstname,
:new.vcfirstname,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcmiddlename<>:new.vcmiddlename) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'vcmiddlename',
:old.vcmiddlename,
:new.vcmiddlename,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vclastname<>:new.vclastname) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```

        'tblDriver',
        'cCitationNumber',
        :old.cCitationNumber,
        'vclastname',
        :old.vclastname,
        :new.vclastname,
        'U',
        USER,
        sysdate,
        null);
END IF;

IF (:old.vcnamesuffix<>:new.vcnamesuffix) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDriver',
     'cCitationNumber',
     :old.cCitationNumber,
     'vcnamesuffix',
     :old.vcnamesuffix,
     :new.vcnamesuffix,
     'U',
     USER,
     sysdate,
     null);
END IF;

IF (:old.vcaddress1<>:new.vcaddress1) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDriver',
     'cCitationNumber',
     :old.cCitationNumber,
     'vcaddress1',
     :old.vcaddress1,
     :new.vcaddress1,
     'U',
     USER,
     sysdate,

```

```

    null);
END IF;

```

```

IF (:old.vcaddress2<>:new.vcaddress2) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcauditcolumnoldvalue,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)

```

```

VALUES

```

```

(seq_tblsyncaudit.nextval,
 'tblDriver',
 'cCitationNumber',
 :old.cCitationNumber,
 'vcaddress2',
 :old.vcaddress2,
 :new.vcaddress2,
 'U',
 USER,
 sysdate,
 null);

```

```

END IF;

```

```

IF (:old.vccity<>:new.vccity) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcauditcolumnoldvalue,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)

```

```

VALUES

```

```

(seq_tblsyncaudit.nextval,
 'tblDriver',
 'cCitationNumber',
 :old.cCitationNumber,
 'vccity',
 :old.vccity,
 :new.vccity,
 'U',
 USER,
 sysdate,
 null);

```

```

END IF;

```

```

IF (:old.cstateorprovince<>:new.cstateorprovince) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,

```

```

vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'cstateorprovince',
:old.cstateorprovince,
:new.cstateorprovince,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcziporpostalcode<>:new.vcziporpostalcode) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'vcziporpostalcode',
:old.vcziporpostalcode,
:new.vcziporpostalcode,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.ddateofbirth<>:new.ddateofbirth) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```

        'tblDriver',
        'cCitationNumber',
        :old.cCitationNumber,
        'ddateofbirth',
        :old.ddateofbirth,
        :new.ddateofbirth,
        'U',
        USER,
        sysdate,
        null);
END IF;

IF (:old.cweight<>:new.cweight) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDriver',
     'cCitationNumber',
     :old.cCitationNumber,
     'cweight',
     :old.cweight,
     :new.cweight,
     'U',
     USER,
     sysdate,
     null);
END IF;

IF (:old.cheight<>:new.cheight) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblDriver',
     'cCitationNumber',
     :old.cCitationNumber,
     'cheight',
     :old.cheight,
     :new.cheight,
     'U',
     USER,
     sysdate,

```

```

    null);
END IF;

IF (:old.chaircolor<>:new.chaircolor) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblDriver',
   'cCitationNumber',
   :old.cCitationNumber,
   'chaircolor',
   :old.chaircolor,
   :new.chaircolor,
   'U',
   USER,
   sysdate,
   null);
END IF;

```

```

IF (:old.ceyecolor<>:new.ceyecolor) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblDriver',
   'cCitationNumber',
   :old.cCitationNumber,
   'ceyecolor',
   :old.ceyecolor,
   :new.ceyecolor,
   'U',
   USER,
   sysdate,
   null);
END IF;

```

```

IF (:old.crace<>:new.crace) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,

```

```

vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'crace',
:old.crace,
:new.crace,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.cgender<>:new.cgender) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'cgender',
:old.cgender,
:new.cgender,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.dlicexpire<>:new.dlicexpire) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```

'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'dlicexpire',
:old.dlicexpire,
:new.dlicexpire,
'U',
USER,
sysdate,
null);
END IF;

```

```
IF (:old.licenseclass<>:new.licenseclass) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'licenseclass',
:old.licenseclass,
:new.licenseclass,
'U',
USER,
sysdate,
null);
```

```
END IF;
```

```
IF (:old.vcdriverlicenseno<>:new.vcdriverlicenseno) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:old.cCitationNumber,
'vcdriverlicenseno',
:old.vcdriverlicenseno,
:new.vcdriverlicenseno,
'U',
USER,
sysdate,
```

```

    null);
END IF;

IF (:old.cdriberlicensestate <>:new.cdriberlicensestate ) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblDriver',
   'cCitationNumber',
   :old.cCitationNumber,
   'cdriberlicensestate ',
   :old.cdriberlicensestate ,
   :new.cdriberlicensestate ,
   'U',
   USER,
   sysdate,
   null);
END IF;
END TRG_SYNCAUDIT_UPD_tblDriver;
/

```

```

CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_INS_tblDriver
AFTER INSERT ON tbldriver
FOR EACH ROW
BEGIN
  -- Inserting selected data into tblsyncAudit table
  INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
  VALUES
    (seq_tblsyncaudit.nextval,
     'tblDriver',
     'cCitationNumber',
     :new.cCitationNumber,
     'cCitationNumber',
     :new.ccitationnumber,
     'I',
     USER,
     sysdate,
     null);

  INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,

```

```
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vcfirstname',  
:new.vcfirstname,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vcmiddlename',  
:new.vcmiddlename,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vclastname',  
:new.vclastname,  
'I',  
USER,
```

```
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'vcnamesuffix',
:new.vcnamesuffix,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'vcaddress1',
:new.vcaddress1,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
```

```
'cCitationNumber',  
:new.cCitationNumber,  
'vcaddress2',  
:new.vcaddress2,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vccity',  
:new.vccity,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cstateorprovince',  
:new.cstateorprovince,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,
```

```
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vcziporpostalcode',  
:new.vcziporpostalcode,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vcdriverlicenseno',  
:new.vcdriverlicenseno,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cdriverlicensestate',  
:new.cdriverlicensestate,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,
```

Photo Radar Schema ISPDEV_ddl.sql

```
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'itelephoneno',  
:new.itelephoneno,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncaudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'ddateofbirth',  
:new.ddateofbirth,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncaudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cgender',  
:new.cgender,  
'I',
```

```

USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'ceyecolor',
:new.ceyecolor,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'chaircolor',
:new.chaircolor,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cweight',  
:new.cweight,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cheight',  
:new.cheight,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'craace',  
:new.craace,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,
```

```

vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'clicenseclass',
:new.clicenseclass,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'dlicissue',
:new.dlicissue,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'dlicexpire',
:new.dlicexpire,
'I',
USER,
sysdate,
null);

```

```

INSERT INTO tblSyncAudit

```

```
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'vcstateidnumber',  
:new.vcstateidnumber,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'cmunicipality',  
:new.cmunicipality,  
'I',  
USER,  
sysdate,  
null);
```

```
INSERT INTO tblSyncAudit  
(iauditid,  
vcAuditTableName,  
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
(seq_tblsyncaudit.nextval,  
'tblDriver',  
'cCitationNumber',  
:new.cCitationNumber,  
'crace',  
:new.crace,
```

```
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'cscalenummer',
:new.cscalenummer,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'ccommercialdriverlicholder',
:new.ccommercialdriverlicholder,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'vcresidencezip',
:new.vcresidencezip,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncaudit
(iauditid,
vCAuditTableName,
vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,
vCAuditColumnNewValue,
vCAuditColumnAction,
vCAuditUpdatedBy,
vCAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblDriver',
'cCitationNumber',
:new.cCitationNumber,
'vcresidencezipsuffix',
:new.vcresidencezipsuffix,
'I',
USER,
sysdate,
null);
```

```
END TRG_SYNCAUDIT_INS_tblDriver;
/
```

-- End of DDL Script for Table ISPDEV.TBLDRIVER

-- Start of DDL Script for Table ISPDEV.TBLINCIDENT
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```
CREATE TABLE ispdev.tblincident
(iincidentid NUMBER NOT NULL,
ccitaitaionnumber VARCHAR2(10),
vcfieldreportnumber VARCHAR2(12),
vcreportnumbercrash VARCHAR2(12),
cinjurydeathindicator CHAR(1),
croadconditions CHAR(1),
cvisibility CHAR(1),
imethodtypeid NUMBER,
vcnotationevidenceseized VARCHAR2(50),
dupdateddate DATE,
iupdatedby NUMBER,
imicrofilmnumber NUMBER,
imicrofilmnumber1 NUMBER)
PCTFREE 10
INITRANS 1
MAXTRANS 255
TABLESPACE ispdev_data
STORAGE (
INITIAL 1048576
```

Photo Radar Schema ISPDEV_ddl.sql

```
MINEXTENTS 1
MAXEXTENTS 2147483645
```

```
)
/
```

-- Constraints for ISPDEV.TBLINCIDENT

```
ALTER TABLE ispdev.tblincident
ADD CONSTRAINT pk_incidentid PRIMARY KEY (iincidentid)
USING INDEX
PCTFREE 10
INITRANS 2
MAXTRANS 255
TABLESPACE ispdev_index
STORAGE (
INITIAL 262144
MINEXTENTS 1
MAXEXTENTS 2147483645
```

```
)
/
```

-- Triggers for ISPDEV.TBLINCIDENT

```
CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_INS_TBLINCIDENT
AFTER INSERT
ON ISPDEV.TBLINCIDENT
REFERENCING NEW AS New OLD AS Old
FOR EACH ROW
BEGIN
```

```
INSERT INTO tblsyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblIncident',
```

```
'IINCIDENTID',:new.IINCIDENTID,
'IINCIDENTID', :new.IINCIDENTID,
'I',USER, sysdate, null);
```

```
INSERT INTO tblsyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
```

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblIncident',
```

```
'IINCIDENTID',:new.IINCIDENTID, 'ccitaitaionnumber', :new.ccitaitaionnumber,
'I',USER, sysdate, null);
```

Photo Radar Schema ISPDEV_ddl.sql

```
IF (:new.IMICROFILMNUMBER<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblIncident',
'IINCIDENTID',:new.IINCIDENTID,
                        'IMICROFILMNUMBER', :new.IMICROFILMNUMBER,
                        'I',USER, sysdate, null);
                        end if;
IF (:new.IMICROFILMNUMBER1<>null) THEN

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblIncident',
'IINCIDENTID',:new.IINCIDENTID,
                        'IMICROFILMNUMBER1', :new.IMICROFILMNUMBER1,
                        'I',USER, sysdate, null);
                        end if;

END TRG_SYNCAUDIT_INS_TBLINCIDENT;
/

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_TBLINCIDENT
AFTER UPDATE
ON ISPDEV.TBLINCIDENT
REFERENCING NEW AS New OLD AS Old
FOR EACH ROW
BEGIN
IF (:old.IMICROFILMNUMBER<>:new.IMICROFILMNUMBER) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
```

```

(seq_tblsyncaudit.nextval,
'tblIncident',
'IINCIDENTID',
:old.IINCIDENTID,
'IMICROFILMNUMBER',
:old.IMICROFILMNUMBER,
:new.IMICROFILMNUMBER,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.IMICROFILMNUMBER1<>:new.IMICROFILMNUMBER1) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblIncident',
'IINCIDENTID',
:old.IINCIDENTID,
'IMICROFILMNUMBER1',
:old.IMICROFILMNUMBER1,
:new.IMICROFILMNUMBER1,
'U',
USER,
sysdate,
null);
END IF;
END TRG_SYNCAUDIT_UPD_TBLINCIDENT;
/

```

```
-- End of DDL Script for Table ISPDEV.TBLINCIDENT
```

```
-- Foreign Key
```

```
ALTER TABLE ispdev.tblincident
ADD CONSTRAINT fk_incident_methodtypeid FOREIGN KEY (imethodtypeid)
REFERENCES ISPDEV.tblmethodtypes (imethodtypeid)
/
```

```
-- End of DDL script for Foreign Key(s)
```

```
-- Start of DDL Script for Table ISPDEV.TBLJURISDICTION
```

```
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop
```

```
CREATE TABLE ispdev.tbljurisdiction
(
  ijurisdictionhistorid NUMBER NOT NULL,
  ijurisdictioncode     NUMBER,
  vcdescription          VARCHAR2(40),
  dcreationdate         DATE,
  vccreatedby           VARCHAR2(30),
  dcreateddate          DATE,
  deffectivedate        DATE,
  tivoid                NUMBER,

```

Photo Radar Schema ISPDEV_ddl.sql

```

    dupdateddate          DATE,
    iupdatedby            NUMBER)
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL     1048576
  MINEXTENTS 1
  MAXEXTENTS 2147483645
)
/

```

-- Constraints for ISPDEV.TBLJURISDICTION

```

ALTER TABLE ispdev.tbljurisdiction
ADD CONSTRAINT pk_jurisdictionid PRIMARY KEY (ijurisdictionhistorid)
USING INDEX
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     65536
  MINEXTENTS 1
  MAXEXTENTS 2147483645
)
/

```

-- Triggers for ISPDEV.TBLJURISDICTION

```

CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_INS_tblJdiction
AFTER INSERT ON tblJurisdiction
FOR EACH ROW
BEGIN
  -- Inserting selected data into tblsyncAudit table
  INSERT INTO tblsyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
  VALUES
    (seq_tblsyncaudit.nextval,
     'tblJurisdiction',
     'ijurisdictionhistorid',
     :new.ijurisdictionhistorid,
     'ijurisdictionhistorid',
     :new.ijurisdictionhistorid,
     'I',
     USER,
     sysdate,
     null);

```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblJurisdiction',
 'ijurisdictionhistorid',
 :new.ijurisdictionhistorid,
 'ijurisdictioncode',
 :new.ijurisdictioncode,
 'I',
 USER,
 sysdate,
 null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblJurisdiction',
 'ijurisdictionhistorid',
 :new.ijurisdictionhistorid,
 'vcdescription',
 :new.vcdescription,
 'I',
 USER,
 sysdate,
 null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblJurisdiction',
 'ijurisdictionhistorid',
 :new.ijurisdictionhistorid,
```

```
'dcreationdate',
:new.dcreationdate,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblJurisdiction',
'ijurisdictionhistorid',
:new.ijurisdictionhistorid,
'vccreatedby',
:new.vccreatedby,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblJurisdiction',
'ijurisdictionhistorid',
:new.ijurisdictionhistorid,
'dcreateddate',
:new.dcreateddate,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
```



```

;new.ijurisdictionhistoricid,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.ijurisdictioncode<>:new.ijurisdictioncode) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblJurisdiction',
'ijurisdictionhistoricid',
:old.ijurisdictionhistoricid,
'ijurisdictioncode',
:old.ijurisdictioncode,
:new.ijurisdictioncode,
'U',
USER,
sysdate,
null);
END IF;
END TRG_SYNCAUDIT_UPD_tblJdiction;
/

```

-- End of DDL Script for Table ISPDEV.TBLJURISDICTION

-- Start of DDL Script for Table ISPDEV.TBLLOCATION
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```

CREATE TABLE ispdev.tbllocation
(
  ilocationhistoricid          NUMBER NOT NULL,
  ilocationcode                NUMBER,
  vcdescription                VARCHAR2(80),
  ijurisdictionhistoricid     NUMBER,
  ispeedlimit                  NUMBER,
  dupdateddate                 DATE,
  iupdatedby                   NUMBER)
PCTFREE          10
INITRANS         1
MAXTRANS         255
TABLESPACE      ispdev_data
STORAGE (
  INITIAL        1048576
  MINEXTENTS    1
  MAXEXTENTS    2147483645
)
/

```

Photo Radar Schema ISPDEV_ddl.sql

-- Indexes for ISPDEV.TBLLOCATION

```
CREATE INDEX ispdev.idx_ilocationcode ON ispdev.tbllocation
(
  ilocationcode          ASC
)
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL      65536
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- Constraints for ISPDEV.TBLLOCATION

```
ALTER TABLE ispdev.tbllocation
ADD CONSTRAINT pk_locatioonhistoricid PRIMARY KEY (ilocationhistoricid)
USING INDEX
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL      65536
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- Triggers for ISPDEV.TBLLOCATION

```
CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_INS_tblLocation
AFTER INSERT ON tblLocation
FOR EACH ROW
BEGIN
-- Inserting selected data into tblSyncAudit table
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblLocation',
   'ilocationhistoricid',
   :new.ilocationhistoricid,
   'ilocationhistoricid',
   :new.ilocationhistoricid,
```

```
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblLocation',
'ilocationhistorid',
:new.ilocationhistorid,
'ilocationcode',
:new.ilocationcode,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblLocation',
'ilocationhistorid',
:new.ilocationhistorid,
'vcdescription',
:new.vcdescription,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
```

```
(seq_tblsyncaudit.nextval,
'tblLocation',
'ilocationhistorid',
:new.ilocationhistorid,
'ijurisdictionhistorid',
:new.ijurisdictionhistorid,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblLocation',
'ilocationhistorid',
:new.ilocationhistorid,
'ispeedlimit',
:new.ispeedlimit,
'I',
USER,
sysdate,
null);
```

```
END TRG_SYNCAUDIT_INS_tblLocation;
/
```

```
CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_UPD_tblLocation
AFTER UPDATE ON tblLocation
FOR EACH ROW
BEGIN
IF (:old.ilocationhistorid<>:new.ilocationhistorid) THEN
INSERT INTO tblSyncaudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblLocation',
'ilocationhistorid',
:old.ilocationhistorid,
'ilocationhistorid',
:old.ilocationhistorid,
:new.ilocationhistorid,
'U',
```

```

    USER,
    sysdate,
    null);
END IF;

IF (:old.ilocationcode<>:new.ilocationcode) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vCAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vCAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblLocation',
   'ilocationhistoricid',
   :old.ilocationhistoricid,
   'ilocationcode',
   :old.ilocationcode,
   :new.ilocationcode,
   'U',
   USER,
   sysdate,
   null);
END IF;
END TRG_SYNCAUDIT_UPD_tblLocation;
/

```

```
-- End of DDL Script for Table ISPDEV.TBLLOCATION
```

```
-- Start of DDL Script for Table ISPDEV.TBLMETHODTYPES
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop
```

```

CREATE TABLE ispdev.tblmethodtypes
  (imethodtypeid          NUMBER NOT NULL,
   vcdescription          VARCHAR2(255),
   dupdateddate          DATE,
   iupdatedby            NUMBER)
PCTFREE          10
INITRANS         1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE (
  INITIAL          1048576
  MINEXTENTS      1
  MAXEXTENTS      2147483645
)
/

```

```
-- Constraints for ISPDEV.TBLMETHODTYPES
```

```
ALTER TABLE ispdev.tblmethodtypes
```

```

ADD CONSTRAINT pk_methodtype PRIMARY KEY (imethodypeid)
USING INDEX
  PCTFREE      10
  INITRANS     2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE     (
    INITIAL      65536
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/

```

-- End of DDL script for Table ISPDEV.TBLMETHODYPES

```

-- Foreign Key
ALTER TABLE ispdev.tblmethodtypes
ADD CONSTRAINT fk_methodtype_userid FOREIGN KEY (iupdatedby)
REFERENCES ISPDEV.tblusers (iuserid)
/

```

-- End of DDL script for Foreign Key(s)
-- Start of DDL Script for Table ISPDEV.TBLOFFICER
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```

CREATE TABLE ispdev.tblofficer
(iofficerhistoricid          NUMBER NOT NULL,
 ibadgenum                   NUMBER,
 ioperatorid                 NUMBER,
 vcofficername               VARCHAR2(60),
 dupdateddate               DATE,
 iupdatedby                  NUMBER,
 dofficerauthorizationdate  DATE,
 isdeleted                   CHAR(1))
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE  ispdev_data
STORAGE     (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- Indexes for ISPDEV.TBLOFFICER

```

CREATE INDEX ispdev.idx_badgenumber ON ispdev.tblofficer
(
  ibadgenum          ASC
)
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE  ispdev_index
STORAGE     (
  INITIAL      65536
  MINEXTENTS  1

```

```

MAXEXTENTS 2147483645
/ )

```

```
-- Constraints for ISPDEV.TBLOFFICER
```

```

ALTER TABLE ispdev.tblofficer
ADD CONSTRAINT pk_officer PRIMARY KEY (iofficerhistoricid)
USING INDEX
  PCTFREE      10
  INITRANS     2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      65536
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/

```

```
-- Triggers for ISPDEV.TBLOFFICER
```

```

CREATE OR REPLACE TRIGGER "ISPDEV".AUD_TBLOFFICER
  AFTER UPDATE OR DELETE ON TBLOFFICER

```

```

  FOR EACH ROW
  Begin

```

```

    insert into TBLOFFICER_AUDIT values (:old.IOFFICERHISTORICID, :old.IBADGENUM,
:old.IOPERATORID, :old.VCOFFICERNAME, :old.DUPDATEDDATE, :old.IUPDATEDBY,
:old.DOFFICERAUTHORIZATIONDATE, :old.ISDELETED);

```

```

End;
/

```

```

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_tblofficer
  AFTER UPDATE ON tblofficer
  FOR EACH ROW
  BEGIN

```

```

  IF (:old.iofficerhistoricid<>:new.iofficerhistoricid) THEN
  INSERT INTO tblsyncAudit

```

```

    (iauditid,
    vcauditTableName,
    vcauditTableIDKeyColumn,
    vcauditTableIDKeyValue,
    vcauditColumnName,
    vcauditcolumnoldvalue,
    vcauditcolumnNewValue,
    vcauditColumnAction,
    vcauditUpdatedBy,
    vcauditUpdatedDate,
    bDidSyncProcessComplete)

```

```

VALUES
  (seq_tblsyncaudit.nextval,
  'tblofficer',
  'iofficerhistoricid',
  :old.iofficerhistoricid,
  'iofficerhistoricid',
  :old.iofficerhistoricid,

```

```

        :new.iofficerhistoricid,
        'U',
        USER,
        sysdate,
        null);
END IF;

IF (:old.ibadgenum<>:new.ibadgenum) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblOfficer',
     'iofficerhistoricid',
     :old.iofficerhistoricid,
     'ibadgenum',
     :old.ibadgenum,
     :new.ibadgenum,
     'U',
     USER,
     sysdate,
     null);
END IF;
IF (:old.IOPERATORID<>:new.IOPERATORID) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     Vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblOfficer',
     'iofficerhistoricid',
     :old.iofficerhistoricid,
     'ioperatorid',
     :old.IOPERATORID,
     :new.IOPERATORID,
     'U',
     USER,
     sysdate,
     null);
END IF;
IF (:old.VCOFFICERNAME<>:new.VCOFFICERNAME) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,

```

Photo Radar Schema ISPDEV_ddl.sql

```
vcAuditTableIDKeyColumn,  
vcAuditTableIDKeyValue,  
vcAuditColumnName,  
Vcauditcolumnoldvalue,  
vcAuditColumnNewValue,  
vcAuditColumnAction,  
vcAuditUpdatedBy,  
vcAuditUpdatedDate,  
bDidSyncProcessComplete)  
VALUES  
  (seq_tblsyncaudit.nextval,  
   'tblOfficer',  
   'iofficerhistoricid',  
   :old.iofficerhistoricid,  
   'vcofficername',  
   :old.VCOFFICERNAME,  
   :new.VCOFFICERNAME,  
   'U',  
   USER,  
   sysdate,  
   null);  
END IF;  
IF (:old.DOFFICERAUTHORIZATIONDATE<>:new.DOFFICERAUTHORIZATIONDATE) THEN  
INSERT INTO tblSyncAudit  
  (iauditid,  
   vcAuditTableName,  
   vcAuditTableIDKeyColumn,  
   vcAuditTableIDKeyValue,  
   vcAuditColumnName,  
   Vcauditcolumnoldvalue,  
   vcAuditColumnNewValue,  
   vcAuditColumnAction,  
   vcAuditUpdatedBy,  
   vcAuditUpdatedDate,  
   bDidSyncProcessComplete)  
VALUES  
  (seq_tblsyncaudit.nextval,  
   'tblOfficer',  
   'iofficerhistoricid',  
   :old.iofficerhistoricid,  
   'dofficeauthorizationdate',  
   :old.DOFFICERAUTHORIZATIONDATE,  
   :new.DOFFICERAUTHORIZATIONDATE,  
   'U',  
   USER,  
   sysdate,  
   null);  
END IF;  
IF (:old.ISDELETED<>:new.ISDELETED) THEN  
INSERT INTO tblSyncAudit  
  (iauditid,  
   vcAuditTableName,  
   vcAuditTableIDKeyColumn,  
   vcAuditTableIDKeyValue,  
   vcAuditColumnName,  
   Vcauditcolumnoldvalue,  
   vcAuditColumnNewValue,  
   vcAuditColumnAction,  
   vcAuditUpdatedBy,  
   vcAuditUpdatedDate,  
   bDidSyncProcessComplete)  
VALUES  
  (seq_tblsyncaudit.nextval,
```

Photo Radar Schema ISPDEV_ddl.sql

```
'tblOfficer',
'iofficerhistoricid',
:old.iofficerhistoricid,
'isdeleted',
:old.ISDELETED,
:new.ISDELETED,
'U',
USER,
sysdate,
null);
END IF;
END TRG_SYNCAUDIT_UPD_tblOfficer;
/
```

```
CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SYNCAUDIT_INS_tblOfficer
AFTER INSERT ON tblOfficer
FOR EACH ROW
```

```
BEGIN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblOfficer',
'iofficerHistoricId',
:new.iofficerhistoricid,
'iofficerHistoricId',
:new.iofficerhistoricid,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblOfficer',
'iofficerHistoricId',
:new.iofficerhistoricid,
'ibadgeNum',
:new.ibadgenum,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblOfficer',
 'iofficerHistoricId',
 :new.iofficerhistoricid,
 'iOperatorId',
 :new.ioperatorid,
 'I',
 USER,
 sysdate,
 null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblOfficer',
 'iofficerhistoricId',
 :new.iofficerhistoricid,
 'vcOfficerName',
 :new.vcofficername,
 'I',
 USER,
 sysdate,
 null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblOfficer',
 'iofficerhistoricId',
 :new.iofficerhistoricid,
```

```
'dofficerAuthorizationDate',
:new.dofficerauthorizationdate,
'I',
USER,
sysdate,
null);
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblOfficer',
'iofficerhistoricid',
:new.iofficerhistoricid,
'isdeleted',
:new.isdeleted,
'I',
USER,
sysdate,
null);
```

```
END TRG_SYNCAUDIT_INS_tblOfficer;
/
```

-- End of DDL Script for Table ISPDEV.TBLOFFICER

-- Start of DDL Script for Table ISPDEV.TBLOFFICER_AUDIT
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```
CREATE TABLE ispdev.tblOfficer_audit
(iofficerhistoricid          NUMBER,
ibadgenum                   NUMBER,
ioperatorid                 NUMBER,
vcofficername               VARCHAR2(60),
dupdateddate                DATE,
iupdatedby                  NUMBER,
dofficerauthorizationdate   DATE,
isdeleted                   CHAR(1))
PCTFREE          10
INITRANS         1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE (
  INITIAL        1048576
  MINEXTENTS     1
  MAXEXTENTS     2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLOFFICER_AUDIT

-- Start of DDL Script for Table ISPDEV.TBLROLES
 -- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```
CREATE TABLE ispdev.tblroles
  (iroleid          NUMBER NOT NULL,
   vcroledescription VARCHAR2(255),
   dupdateddate    DATE,
   iupdatedby      NUMBER)
PCTFREE          10
INITTRANS        1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE (
  INITIAL         1048576
  MINEXTENTS      1
  MAXEXTENTS     2147483645
)
/
```

-- Constraints for ISPDEV.TBLROLES

```
ALTER TABLE ispdev.tblroles
ADD CONSTRAINT pk_roleid PRIMARY KEY (iroleid)
USING INDEX
PCTFREE          10
INITTRANS        2
MAXTRANS         255
TABLESPACE       ispdev_index
STORAGE (
  INITIAL         65536
  MINEXTENTS      1
  MAXEXTENTS     2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLROLES

-- Start of DDL Script for Table ISPDEV.TBLSTATUS
 -- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```
CREATE TABLE ispdev.tblstatus
  (istatusid       NUMBER NOT NULL,
   vcstatusdescription VARCHAR2(100),
   dupdateddate    DATE,
   iupdatedby      NUMBER)
PCTFREE          10
INITTRANS        1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE (
  INITIAL         1048576
  MINEXTENTS      1
  MAXEXTENTS     2147483645
)
/
```

Photo Radar Schema ISPDEV_ddl.sql

-- Constraints for ISPDEV.TBLSTATUS

```
ALTER TABLE ispdev.tblstatus
ADD CONSTRAINT pk_statusid PRIMARY KEY (istatusid)
USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      65536
    MINEXTENTS   1
    MAXEXTENTS  2147483645
  )
/
```

-- End of DDL Script for Table ISPDEV.TBLSTATUS

-- Start of DDL Script for Table ISPDEV.TBLSYNCAUDIT
-- Generated 22-Apr-2009 15:31:40 from ISPDEV@photop

```
CREATE TABLE ispdev.tblsyncaudit
(iauditid          NUMBER NOT NULL,
 vcaudittablename VARCHAR2(255) NOT NULL,
 vcaudittableidkeycolumn VARCHAR2(255),
 vcaudittableidkeyvalue  VARCHAR2(1000),
 vcauditcolumnname     VARCHAR2(255) NOT NULL,
 vcauditcolumnoldvalue  VARCHAR2(1000),
 vcauditcolumnnewvalue  VARCHAR2(1000),
 vcauditcolumnaction    CHAR(1),
 vcauditupdatedby      VARCHAR2(255) NOT NULL,
 vcauditupdateddate    DATE,
 bdidsyncprocesscomplete CHAR(1))
PCTFREE      10
INITTRANS    1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE (
  INITIAL      2097152
  MINEXTENTS   1
  MAXEXTENTS  2147483645
)
/
```

-- Indexes for ISPDEV.TBLSYNCAUDIT

```
CREATE INDEX ispdev.idx_syncaudit_tablename ON ispdev.tblsyncaudit
(
  vcaudittablename          ASC
)
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_index
```

Photo Radar Schema ISPDEV_ddl.sql

```

STORAGE (
  INITIAL      150994944
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

```

CREATE INDEX ispdev.idx_syncaudit_tablekeycol ON ispdev.tblsyncaudit
(
  vcaudittableidkeycolumn          ASC
)
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE (
  INITIAL      176160768
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

```

CREATE BITMAP INDEX ispdev.idx_syncaudit_colaction ON ispdev.tblsyncaudit
(
  vcauditcolumnaction              ASC
)
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE (
  INITIAL      2097152
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- Constraints for ISPDEV.TBLSYNCAUDIT

```

ALTER TABLE ispdev.tblsyncaudit
ADD CONSTRAINT pk_tblsyncaudit_iauditid PRIMARY KEY (iauditid)
USING INDEX
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE (
  INITIAL      75497472
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- End of DDL Script for Table ISPDEV.TBLSYNCAUDIT

-- Start of DDL Script for Table ISPDEV.TBLSYNCDetaillog
-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```

CREATE TABLE ispdev.tblsyncdetaillog
(isyncdetailid          NUMBER NOT NULL,

```

Photo Radar Schema ISPDEV_ddl.sql

```

isyncbatchid          NUMBER NOT NULL,
vcsyncerrordescription VARCHAR2(2000),
vcsynctablename      VARCHAR2(255),
vcsynckeycolumnname  VARCHAR2(255),
vcsynckeycolumnvalue VARCHAR2(255),
vcsyncerrorfilepath  VARCHAR2(255),
bsyncstatus          NUMBER,
dsyncerrordate       DATE,
iauditid             NUMBER)
PCTFREE              10
INITRANS             1
MAXTRANS             255
TABLESPACE           ispdev_data
STORAGE (
  INITIAL            1048576
  MINEXTENTS         1
  MAXEXTENTS         2147483645
)

```

/)

-- Constraints for ISPDEV.TBLSYNCDetailLog

```

ALTER TABLE ispdev.tblsyncdetaillog
ADD CONSTRAINT pk_isyncdtllog_isyncdtlid PRIMARY KEY (isyncdetailid)
USING INDEX
PCTFREE          10
INITRANS         2
MAXTRANS         255
TABLESPACE       ispdev_index
STORAGE (
  INITIAL         2097152
  MINEXTENTS     1
  MAXEXTENTS     2147483645
)

```

/)

-- Triggers for ISPDEV.TBLSYNCDetailLog

```

CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SyncDetailLog_INS_SyncLog
AFTER INSERT ON tblSyncDetailLog
FOR EACH ROW
DECLARE in_Count INTEGER;

```

BEGIN

```

SELECT COUNT(*) INTO in_Count
FROM   tblSyncDetailLog
WHERE  iSyncBatchID = :NEW.iSyncBatchID
AND    bSyncStatus = 0;

IF (in_Count > 0) THEN
  UPDATE tblSyncLog
  SET    bSyncStatus = 0
  WHERE  iSyncBatchID = :NEW.iSyncBatchID;
ELSE
  UPDATE tblSyncLog
  SET    bSyncStatus = 1

```

```

                                Photo Radar Schema ISPDEV_ddl.sql
                                WHERE      iSyncBatchID = :NEW.iSyncBatchID;
END IF;
END TRG_SyncDetailLog_INS_SyncLog;
/

```

```

CREATE OR REPLACE TRIGGER "ISPDEV".TRG_SyncDetailLog_UPD_SyncLog
AFTER UPDATE ON tblSyncDetailLog
FOR EACH ROW
DECLARE in_Count INTEGER;

```

```

BEGIN

```

```

    SELECT  COUNT(*) INTO in_Count
    FROM    tblSyncDetailLog
    WHERE   iSyncBatchID = :OLD.iSyncBatchID
    AND     bSyncStatus = 0;

```

```

    IF (in_Count > 0) THEN
        UPDATE  tblSyncLog
        SET     bSyncStatus = 0
        WHERE   iSyncBatchID = :OLD.iSyncBatchID;
    ELSE

```

```

        UPDATE  tblSyncLog
        SET     bSyncStatus = 1
        WHERE   iSyncBatchID = :OLD.iSyncBatchID;

```

```

    END IF;
END TRG_SyncDetailLog_UPD_SyncLog;
/

```

```

-- End of DDL Script for Table ISPDEV.TBLSYNCDetailLog

```

```

-- Foreign Key

```

```

ALTER TABLE ispdev.tblsyncdetaillog
ADD CONSTRAINT fk_isyncdtllog_isyncbatchid FOREIGN KEY (isyncbatchid)
REFERENCES ISPDEV.tblsynclog (isyncbatchid)
/

```

```

-- End of DDL script for Foreign Key(s)

```

```

-- Start of DDL Script for Table ISPDEV.TBLSYNCLOG

```

```

-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```

```

CREATE TABLE ispdev.tblsynclog
(isyncbatchid          NUMBER NOT NULL,
dsyncdate             DATE NOT NULL,
isyncrecordcount      NUMBER NOT NULL,
bsyncstatus           CHAR(1),
bsyncmailsentstatus   CHAR(1),
vcsyncexecutedby     VARCHAR2(50) NOT NULL,
isyncacsbatchid       NUMBER)
PCTFREE              10
INITRANS              1
MAXTRANS              255
TABLESPACE            ispdev_data
STORAGE (
    INITIAL            1048576
    MINEXTENTS         1
    MAXEXTENTS         2147483645
)
/

```

Photo Radar Schema ISPDEV_ddl.sql

-- Constraints for ISPDEV.TBLSYNCLLOG

```
ALTER TABLE ispdev.tblsynclog
ADD CONSTRAINT pk_tblsynclog_isyncbatchid PRIMARY KEY (isyncbatchid)
USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      65536
    MINEXTENTS   1
    MAXEXTENTS  2147483645
  )
/
```

-- End of DDL Script for Table ISPDEV.TBLSYNCLLOG

-- Start of DDL Script for Table ISPDEV.TBLTYPECODE
-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```
CREATE TABLE ispdev.tbltypecode
  (itypecode          NUMBER NOT NULL,
  vctypedescription  VARCHAR2(100) NOT NULL,
  vcacsvalue         VARCHAR2(100),
  vcispvalue         VARCHAR2(100))
  PCTFREE      10
  INITTRANS    1
  MAXTRANS     255
  TABLESPACE  ispdev_data
  STORAGE (
    INITIAL      1048576
    MINEXTENTS   1
    MAXEXTENTS  2147483645
  )
/
```

-- Constraints for ISPDEV.TBLTYPECODE

```
ALTER TABLE ispdev.tbltypecode
ADD CONSTRAINT pk_tbltypecode_itypecode PRIMARY KEY (itypecode)
USING INDEX
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      65536
    MINEXTENTS   1
    MAXEXTENTS  2147483645
  )
/
```

-- End of DDL Script for Table ISPDEV.TBLTYPECODE

-- start of DDL Script for Table ISPDEV.TBLUSERS

-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```
CREATE TABLE ispdev.tblusers
  (iuserid          NUMBER NOT NULL,
   vcusername       VARCHAR2(255),
   vcemailid        VARCHAR2(255),
   gpassword         VARCHAR2(255),
   dupdateddate     DATE,
   iupdatedby       NUMBER,
   userlevel         CHAR(1),
   isdeleted         CHAR(1))
PCTFREE          10
INITRANS         1
MAXTRANS         255
TABLESPACE        ispdev_data
STORAGE (
  INITIAL          1048576
  MINEXTENTS       1
  MAXEXTENTS       2147483645
)
/
```

-- Constraints for ISPDEV.TBLUSERS

```
ALTER TABLE ispdev.tblusers
ADD CONSTRAINT pk_userid PRIMARY KEY (iuserid)
USING INDEX
PCTFREE          10
INITRANS         2
MAXTRANS         255
TABLESPACE        ispdev_index
STORAGE (
  INITIAL          65536
  MINEXTENTS       1
  MAXEXTENTS       2147483645
)
/
```

-- Triggers for ISPDEV.TBLUSERS

```
CREATE OR REPLACE TRIGGER ISPDEV.TRG_AUDIT_UPD_TBLUSERS
AFTER UPDATE ON TBLUSERS
FOR EACH ROW
BEGIN

  INSERT INTO TBLUSERS_AUDIT
VALUES(:old.IUSERID, :old.VCUSERNAME, :old.VCEMAILID, :old.GPASSWORD, :old.DUPDATEDDATE,
:old.IUPDATEDBY, :old.USERLEVEL, :old.ISDELETED);

END TRG_AUDIT_UPD_TBLUSERS;
/
```

```
CREATE OR REPLACE TRIGGER ISPDEV.TRIGGER_AUD_TBLUSERS
AFTER UPDATE OR DELETE ON TBLUSERS
FOR EACH ROW
BEGIN

  INSERT INTO TBLUSERS_AUDIT
```

```

Photo Radar Schema ISPDEV_ddl.sql
VALUES(:old.IUSERID,:old.VCUSERNAME,:old.VCEMAILID,:old.GPASSWORD,:old.DUPDATEDDATE,
:old.IUPDATEDBY,:old.USERLEVEL,:old.ISDELETED);

END TRIGGER_AUD_TBLUSERS;
/

CREATE OR REPLACE TRIGGER "ISPDEV".AUD_TBLUSERS
  AFTER UPDATE OR DELETE ON TBLUSERS
  FOR EACH ROW
Begin
  insert into TBLUSERS_AUDIT values (:old.IUSERID,
:old.VCUSERNAME, :old.VCEMAILID, :old.GPASSWORD, :old.DUPDATEDDATE, :old.IUPDATEDBY,
:old.USERLEVEL, :old.ISDELETED);

End;
/

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_INS_tblUsers
AFTER INSERT
ON TBLUSERS
FOR EACH ROW
BEGIN
  INSERT INTO tblsyncAudit
    (iauditid,
    vcAuditTableName,
    vcAuditTableIDKeyColumn,
    vcAuditTableIDKeyValue,
    vcAuditColumnName,
    vcAuditColumnNewValue,
    vcAuditColumnAction,
    vcAuditUpdatedBy,
    vcAuditUpdatedDate,
    bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
  'tblUsers',
  'iUserId',
  :new.IUSERID,
  'iUserId',
  :new.IUSERID,
  'I',
  USER,
  sysdate,
  null);

  INSERT INTO tblsyncAudit
    (iauditid,
    vcAuditTableName,
    vcAuditTableIDKeyColumn,
    vcAuditTableIDKeyValue,
    vcAuditColumnName,
    vcAuditColumnNewValue,
    vcAuditColumnAction,
    vcAuditUpdatedBy,
    vcAuditUpdatedDate,
    bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
  'tblUsers',
  'iUserId',

```

```

        :new.IUSERID,
        'vcUserName',
        :new.VCUSERNAME,
        'I',
        USER,
        sysdate,
        null);

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblUsers',
 'iUserId',
 :new.IUSERID,
 'UserLevel',
 :new.USERLEVEL,
 'I',
 USER,
 sysdate,
 null);

END TRG_SYNCAUDIT_INS_tblUsers;
/

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_TBLUSERS
AFTER UPDATE
ON TBLUSERS
FOR EACH ROW
BEGIN
-- your code here
IF (:old.IUSERID<>:new.IUSERID) THEN
INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcAuditColumnOldValue,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
 'tblUsers',
 'iUserId',
 :old.iUserId,
 'iUserId',
 :old.IUSERID,
 :new.IUSERID,
 'U',
 USER,

```

```

        sysdate,
        null);
END IF;
IF (:old.VCUSERNAME<>:new.VCUSERNAME) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblUsers',
     'iUserId',
     :old.iUserId,
     'vcUserName',
     :old.VCUSERNAME,
     :new.VCUSERNAME,
     'U',
     USER,
     sysdate,
     null);
END IF;

```

```

IF (:old.USERLEVEL<>:new.USERLEVEL) THEN
INSERT INTO tblSyncAudit
    (iauditid,
     vcAuditTableName,
     vcAuditTableIDKeyColumn,
     vcAuditTableIDKeyValue,
     vcAuditColumnName,
     vcauditcolumnoldvalue,
     vcAuditColumnNewValue,
     vcAuditColumnAction,
     vcAuditUpdatedBy,
     vcAuditUpdatedDate,
     bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
     'tblUsers',
     'iUserId',
     :old.iUserId,
     'UserLevel',
     :old.USERLEVEL,
     :new.USERLEVEL,
     'U',
     USER,
     sysdate,
     null);
END IF;

```

```

END TRG_SYNCAUDIT_UPD_TBLUSERS;
/

```

```

-- End of DDL script for Table ISPDEV.TBLUSERS
Page 83

```

Photo Radar Schema ISPDEV_ddl.sql

-- Start of DDL Script for Table ISPDEV.TBLUSERS_AUDIT
-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```
CREATE TABLE ispdev.tblusers_audit
  (iuserid          NUMBER,
   vcusername       VARCHAR2(255),
   vcemailid        VARCHAR2(255),
   gpassword         VARCHAR2(255),
   dupdateddate     DATE,
   iupdatedby       NUMBER,
   userlevel         CHAR(1),
   isdeleted         CHAR(1))
PCTFREE      10
INITRANS     1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL     1048576
  MINEXTENTS 1
  MAXEXTENTS 2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLUSERS_AUDIT

-- Start of DDL Script for Table ISPDEV.TBLVIOLATION
-- Generated 22-Apr-2009 15:31:41 from ISPDEV@photop

```
CREATE TABLE ispdev.tblviolation
  (ccitationnumber  VARCHAR2(10) NOT NULL,
   ideploymentid    NUMBER,
   dviolationdate   DATE,
   tviolationtime   VARCHAR2(10),
   vcvehregistrationnoormvid VARCHAR2(20),
   vcvehiclelicenseno VARCHAR2(12),
   cvehstateorprovince VARCHAR2(2),
   vcvehiclemake    VARCHAR2(15),
   cvehmodel        CHAR(2),
   vcvehstyle       VARCHAR2(10),
   ivehicleyear     VARCHAR2(4),
   vcvehiclecolor   VARCHAR2(6),
   iamountoffline   NUMBER,
   dissuedate       DATE,
   dissuedate06     DATE,
   icourtappearancerequired CHAR(1),
   dcourtappearancedate DATE,
   icourtid         NUMBER,
   ilocationhistorid NUMBER,
   iweathercode     NUMBER,
   cdirection       CHAR(1),
   istatus          NUMBER,
   vcviewedby       VARCHAR2(60),
   vcverifiedby     VARCHAR2(60),
   vcerror           VARCHAR2(60),
   icategorycode    NUMBER,
   ttimestamp       VARCHAR2(10),
   vcoriginalticket VARCHAR2(20),
   vcnotes          VARCHAR2(60),
   )
```

Photo Radar Schema ISPDEV_ddl.sql

```

cvehicledescription      VARCHAR2(80),
ispeed                   NUMBER,
ispeedlimit              NUMBER,
ireducedspeed            NUMBER,
iofficerhistoricid      NUMBER,
dissueddate10           DATE,
ijurisdictionhistoricid NUMBER,
ccircuitcourtncciccode  CHAR(4),
vcdistrictofassignment  VARCHAR2(4),
vcarrestingagencyciccode VARCHAR2(9),
vcdocumentcontrolnumber VARCHAR2(9),
vccasesequencenumber    NUMBER,
vctownshipname          VARCHAR2(20),
ctownshiproadflag       CHAR(1),
campindicator            CHAR(2),
cregistrationyearlicenseplate CHAR(4),
vcusdotnumber           VARCHAR2(7),
vccounty                 CHAR(3),
vccityvillage           VARCHAR2(25),
dupdateddate            DATE,
iupdatedby              NUMBER,
vcdocumenttype          CHAR(1) DEFAULT 'C',
cvehicletype            CHAR(2),
ccourtappearancetime    VARCHAR2(5),
vcdistrictofoccurrence  VARCHAR2(4),
vccontrabandtypecode    CHAR(1),
dposteddate             DATE DEFAULT sysdate)
PCTFREE      10
INITTRANS    1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL     3145728
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

-- Indexes for ISPDEV.TBLVIOLATION

```

CREATE INDEX ispdev.idx_dissuedate ON ispdev.tblviolation
(
  dissuedate          ASC
)
PCTFREE      10
INITTRANS     2
MAXTRANS     255
TABLESPACE    ispdev_index
STORAGE      (
  INITIAL     327680
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

```

```

CREATE INDEX ispdev.idx_vcvehlicno ON ispdev.tblviolation
(
  vcvehiclelicenseno  ASC
)

```

```

PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     327680
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

CREATE INDEX ispdev.idx_istatus ON ispdev.tblviolation
(
  istatus                                ASC
)
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     262144
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

CREATE INDEX ispdev.idx_vcviewedby ON ispdev.tblviolation
(
  vcviewedby                              ASC
)
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     327680
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

CREATE INDEX ispdev.idx_ideployid ON ispdev.tblviolation
(
  ideploymentid                          ASC
)
PCTFREE      10
INITTRANS    2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     262144
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/

-- Constraints for ISPDEV.TBLVIOLATION

ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT chk_campmindicator CHECK (CAMPINDICATOR IN ('A','P'))
/

```

Photo Radar Schema ISPDEV_ddl.sql

```
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT chk_vcdoctype CHECK (VCDOCUMENTTYPE IN ('C','O', 'W'))
/
```

```
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT pk_citationnumber PRIMARY KEY (ccitationnumber)
USING INDEX
PCTFREE      10
INITRANS     2
MAXTRANS     255
TABLESPACE   ispdev_index
STORAGE      (
  INITIAL     327680
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

```
ALTER TABLE ispdev.tblviolation
ADD CHECK (CVEHICLETYPE IN ('00','01', '02', '03', '04', '05', '06', '07', '08',
                             '09', '10', '11', '12', '13','98'))
/
```

-- Triggers for ISPDEV.TBLVIOLATION

```
CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_INS_TBLVIOLATION
AFTER INSERT
ON ISPDEV.TBLVIOLATION
REFERENCING NEW AS NEW OLD AS OLD
FOR EACH ROW
BEGIN
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.ccitationnumber,
'cCitationNumber', :new.ccitationnumber,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.ccitationnumber,
'iDeploymentId', :new.ideploymentid,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
```

Photo Radar Schema ISPDEV_ddl.sql

```
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'dViolationDate', :new.dviolationdate,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
    vCAuditColumnName,vCAuditColumnNewValue,
    vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'tViolationTime', :new.tviolationtime,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
    vCAuditColumnName,vCAuditColumnNewValue,
    vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcVehRegistrationNoOrMVID',
: new.vcvehregistrationnoormvid,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
    vCAuditColumnName,vCAuditColumnNewValue,
    vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcVehicleLicenseNo', :new.vcvehiclelicenseno,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
    vCAuditColumnName,vCAuditColumnNewValue,
    vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'cVehStateOrProvince', :new.cvehstateorprovince,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
    vCAuditColumnName,vCAuditColumnNewValue,
    vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcVehicleMake', :new.vcvehiclemake,
```

Photo Radar Schema ISPDEV_ddl.sql
'I',USER, sysdate, null));

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
                        'cVehModel', :new.cvehmodel,
                        'I',USER, sysdate, null));
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
                        'vcVehStyle', :new.vcvehstyle,
                        'I',USER, sysdate, null));
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
                        'ivehicleYear', :new.ivehicleyear,
                        'I',USER, sysdate, null));
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
                        'vcVehicleColor', :new.vcvehiclecolor,
                        'I',USER, sysdate, null));
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
                        ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
                        'iAmountOfFine', :new.iamountoffine,
                        'I',USER, sysdate, null));
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
                        vcAuditColumnName,vcAuditColumnNewValue,
                        vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
```

Photo Radar Schema ISPDEV_ddl.sql

```

VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'dIssueDate', :new.dissuedate,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'dIssueDate06', :new.dIssueDate06,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iCourtAppearanceRequired', :new.icourtappearancerequired,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'dCourtAppearanceDate', :new.dcourtappearancedate,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iCourtId', :new.icourtId,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iLocationHistoricId', :new.ilocationhistoricid,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,

```

Photo Radar Schema ISPDEV_ddl.sql

```
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iweatherCode', :new.iweathercode,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'cDirection', :new.cdirection,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iStatus', :new.istatus,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcViewedBy', :new.vcviewedby,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcVerifiedBy', :new.vcverifiedby,
'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcError', :new.vcerror,
'I',USER, sysdate, null);
```

Photo Radar Schema ISPDEV_ddl.sql

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'iCategoryCode', :new.icategorycode,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'tTimeStamp', :new.ttimestamp,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcOriginalTicket', :new.vcoriginalticket,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcNotes', :new.vcnotes,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'cVehicleDescription', :new.cvehicledescription,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,vcAuditColumnNewValue,
vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
```

```
( seq_tblsyncaudit.nextval, 'tblViolation',
```

Photo Radar Schema ISPDEV_ddl.sql

```
'cCitationNumber',:new.cCitationNumber,
      'iSpeed', :new.ispeed,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'iSpeedLimit', :new.ispeedlimit,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'iReducedSpeed', :new.ireducedspeed,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'iOfficerHistoricId', :new.iofficerhistoricid,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'dIssuedDate10', :new.dissueddate10,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'iJurisdictionHistoricId', :new.ijurisdictionhistoricid,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
```

Photo Radar Schema ISPDEV_ddl.sql

```

vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'cCircuitCourtNCICCode', :new.ccircuitcourtncciccode,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
    vcAuditColumnName,vcAuditColumnNewValue,
    vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcDistrictOfAssignment', :new.vcdistrictofassignment,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
    vcAuditColumnName,vcAuditColumnNewValue,
    vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcArrestingAgencyNCICCode',
:new.vcarrestingagencyncciccode,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
    vcAuditColumnName,vcAuditColumnNewValue,
    vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcDocumentControlNumber', :new.vcdocumentcontrolnumber,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
    vcAuditColumnName,vcAuditColumnNewValue,
    vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcCaseSequenceNumber', :new.vccasesequencenumber,
    'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
    vcAuditColumnName,vcAuditColumnNewValue,
    vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
    ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
    'vcTownshipName', :new.vctownshipname,
    'I',USER, sysdate, null);

```

Photo Radar Schema ISPDEV_ddl.sql

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'cTownshipRoadFlag', :new.ctownshiproadflag,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'cAMPIndicator', :new.campindicator,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'cRegistrationYearLicensePlate',
:new.cregistrationyearlicenseplate,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcusdotnumber', :new.vcusdotnumber,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
'vcCounty', :new.vccounty,
'I',USER, sysdate, null);
```

```
INSERT INTO tblSyncAudit ( iauditid, vCAuditTableName, vCAuditTableIDKeyColumn,
vCAuditTableIDKeyValue,
vCAuditColumnName,vCAuditColumnNewValue,
vCAuditColumnAction,vCAuditUpdatedBy,
vCAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
( seq_tblsyncaudit.nextval, 'tblViolation',
```

```

Photo Radar Schema ISPDEV_ddl.sql
'cCitationNumber',:new.cCitationNumber,
      'vcCityVillage', :new.vccityvillage,
      'I',USER, sysdate, null);

INSERT INTO tblSyncAudit ( iauditid, vcAuditTableName, vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
      vcAuditColumnName,vcAuditColumnNewValue,
      vcAuditColumnAction,vcAuditUpdatedBy,
vcAuditUpdatedDate,bDidSyncProcessComplete)
VALUES
      ( seq_tblsyncaudit.nextval, 'tblViolation',
'cCitationNumber',:new.cCitationNumber,
      'vcDocumentType', :new.vcdocumenttype,
      'I',USER, sysdate, null);

END TRG_SYNCAUDIT_INS_tblViolation;
/

CREATE OR REPLACE TRIGGER ISPDEV.TRG_SYNCAUDIT_UPD_tblViolation
AFTER UPDATE ON tblViolation
FOR EACH ROW
BEGIN
IF (:old.ccitationnumber<>:new.ccitationnumber) THEN
INSERT INTO tblSyncAudit
      (iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
      (seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'cCitationNumber',
:old.ccitationnumber,
:new.ccitationnumber,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcdistrictofassignment<>:new.vcdistrictofassignment) THEN
INSERT INTO tblSyncAudit
      (iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES

```

```

(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vcDistrictOfAssignment',
:old.vcdistrictofassignment,
:new.vcdistrictofassignment,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcarrestingagencyciccode<>:new.vcarrestingagencyciccode) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vcarrestingagencyciccode',
:old.vcarrestingagencyciccode,
:new.vcarrestingagencyciccode,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vctownshipname<>:new.vctownshipname) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vctownshipname',
:old.vctownshipname,
:new.vctownshipname,
'U',
USER,

```

```

    sysdate,
    null);
END IF;

IF (:old.dviolationdate<>:new.dviolationdate) THEN
INSERT INTO tblSyncAudit
    (iauditid,
    vCAuditTableName,
    vCAuditTableIDKeyColumn,
    vCAuditTableIDKeyValue,
    vCAuditColumnName,
    vCAuditColumnOldValue,
    vCAuditColumnNewValue,
    vCAuditColumnAction,
    vCAuditUpdatedBy,
    vCAuditUpdatedDate,
    bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
    'tblViolation',
    'cCitationNumber',
    :old.cCitationNumber,
    'dviolationdate',
    :old.dviolationdate,
    :new.dviolationdate,
    'U',
    USER,
    sysdate,
    null);
END IF;

```

```

IF (:old.tviolationtime<>:new.tviolationtime) THEN
INSERT INTO tblSyncAudit
    (iauditid,
    vCAuditTableName,
    vCAuditTableIDKeyColumn,
    vCAuditTableIDKeyValue,
    vCAuditColumnName,
    vCAuditColumnOldValue,
    vCAuditColumnNewValue,
    vCAuditColumnAction,
    vCAuditUpdatedBy,
    vCAuditUpdatedDate,
    bDidSyncProcessComplete)
VALUES
    (seq_tblsyncaudit.nextval,
    'tblViolation',
    'cCitationNumber',
    :old.cCitationNumber,
    'tviolationtime',
    :old.tviolationtime,
    :new.tviolationtime,
    'U',
    USER,
    sysdate,
    null);
END IF;

```

```

IF (:old.campmindicator<>:new.campmindicator) THEN
INSERT INTO tblSyncAudit
    (iauditid,
    vCAuditTableName,
    vCAuditTableIDKeyColumn,

```

```

vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'campindicator',
:old.campindicator,
:new.campindicator,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcvehregistrationnoormvid<>:new.vcvehregistrationnoormvid) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vcvehregistrationnoormvid',
:old.vcvehregistrationnoormvid,
:new.vcvehregistrationnoormvid,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.VCVEHICLELICENSENO<>:new.VCVEHICLELICENSENO) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES

```

```

(seq_tblsyncaudit.nextval,
'tblviolation',
'cCitationNumber',
:old.cCitationNumber,
'vcvehiclelicenseno',
:old.VCVEHICLELICENSENSO,
:new.VCVEHICLELICENSENSO,
'U',
USER,
sysdate,
null);
END IF;
IF (:old.cvehstateorprovince<>:new.cvehstateorprovince) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblviolation',
'cCitationNumber',
:old.cCitationNumber,
'cvehstateorprovince',
:old.cvehstateorprovince,
:new.cvehstateorprovince,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.vcvehiclemake<>:new.vcvehiclemake) THEN
INSERT INTO tblsyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblviolation',
'cCitationNumber',
:old.cCitationNumber,
'vcvehiclemake',
:old.vcvehiclemake,
:new.vcvehiclemake,
'U',
USER,
sysdate,

```

```

    null);
END IF;

IF (:old.vcvehiclecolor<>:new.vcvehiclecolor) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblViolation',
   'cCitationNumber',
   :old.cCitationNumber,
   'vcvehiclecolor',
   :old.vcvehiclecolor,
   :new.vcvehiclecolor,
   'U',
   USER,
   sysdate,
   null);
END IF;

```

```

IF (:old.cvehmodel<>:new.cvehmodel) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,
   vcAuditColumnName,
   vcauditcolumnoldvalue,
   vcAuditColumnNewValue,
   vcAuditColumnAction,
   vcAuditUpdatedBy,
   vcAuditUpdatedDate,
   bDidSyncProcessComplete)
VALUES
  (seq_tblsyncaudit.nextval,
   'tblViolation',
   'cCitationNumber',
   :old.cCitationNumber,
   'cvehmodel',
   :old.cvehmodel,
   :new.cvehmodel,
   'U',
   USER,
   sysdate,
   null);
END IF;

```

```

IF (:old.vcvehstyle<>:new.vcvehstyle) THEN
INSERT INTO tblSyncAudit
  (iauditid,
   vcAuditTableName,
   vcAuditTableIDKeyColumn,
   vcAuditTableIDKeyValue,

```

```

vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vcvehstyle',
:old.vcvehstyle,
:new.vcvehstyle,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.ivehicleyear<>:new.ivehicleyear) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'vehicleyear',
:old.ivehicleyear,
:new.ivehicleyear,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.cdirection<>:new.cdirection) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```

'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'cdirection',
:old.cdirection,
:new.cdirection,
'U',
USER,
sysdate,
null);
END IF;

```

```

IF (:old.ispeed<>:new.ispeed) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)

```

```

VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'ispeed',
:old.ispeed,
:new.ispeed,
'U',
USER,
sysdate,
null);
END IF;

```

```

IF (:old.ispeedlimit<>:new.ispeedlimit) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)

```

```

VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'ispeedlimit',
:old.ispeedlimit,
:new.ispeedlimit,
'U',
USER,
sysdate,

```

```

    null);
END IF;

```

```

IF (:old.vcnotes<>:new.vcnotes) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcauditcolumnoldvalue,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)

```

```

VALUES

```

```

(seq_tblsyncaudit.nextval,
 'tblViolation',
 'cCitationNumber',
 :old.cCitationNumber,
 'vcnotes',
 :old.vcnotes,
 :new.vcnotes,
 'U',
 USER,
 sysdate,
 null);

```

```

END IF;

```

```

IF (:old.iweathercode<>:new.iweathercode) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,
 vcAuditColumnName,
 vcauditcolumnoldvalue,
 vcAuditColumnNewValue,
 vcAuditColumnAction,
 vcAuditUpdatedBy,
 vcAuditUpdatedDate,
 bDidSyncProcessComplete)

```

```

VALUES

```

```

(seq_tblsyncaudit.nextval,
 'tblViolation',
 'cCitationNumber',
 :old.cCitationNumber,
 'iweathercode',
 :old.iweathercode,
 :new.iweathercode,
 'U',
 USER,
 sysdate,
 null);

```

```

END IF;

```

```

IF (:old.dissuedate<>:new.dissuedate) THEN

```

```

INSERT INTO tblSyncAudit
(iauditid,
 vcAuditTableName,
 vcAuditTableIDKeyColumn,
 vcAuditTableIDKeyValue,

```

```

vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'dissuedate',
:old.dissuedate,
:new.dissuedate,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.dcourtappearancedate<>:new.dcourtappearancedate) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'dcourtappearancedate',
:old.dcourtappearancedate,
:new.dcourtappearancedate,
'U',
USER,
sysdate,
null);
END IF;

IF (:old.icourtappearancerequired<>:new.icourtappearancerequired) THEN
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
VALUES
(seq_tblsyncaudit.nextval,

```

```

'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'ccourtappearancerequired',
:old.icourtappearancerequired,
:new.icourtappearancerequired,
'U',
USER,
sysdate,
null);
END IF;

```

```
IF (:old.ISTATUS<>:new.ISTATUS) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'ISTATUS',
:old.ISTATUS,
:new.ISTATUS,
'U',
USER,
sysdate,
null);
END IF;
```

```
IF (:old.IAMOUNTOFFINE<>:new.IAMOUNTOFFINE) THEN
```

```
INSERT INTO tblSyncAudit
(iauditid,
vcAuditTableName,
vcAuditTableIDKeyColumn,
vcAuditTableIDKeyValue,
vcAuditColumnName,
Vcauditcolumnoldvalue,
vcAuditColumnNewValue,
vcAuditColumnAction,
vcAuditUpdatedBy,
vcAuditUpdatedDate,
bDidSyncProcessComplete)
```

```
VALUES
(seq_tblsyncaudit.nextval,
'tblViolation',
'cCitationNumber',
:old.cCitationNumber,
'IAMOUNTOFFINE',
:old.IAMOUNTOFFINE,
:new.IAMOUNTOFFINE,
'U',
USER,
sysdate,
```

```

null);
END IF;

END TRG_SYNCAUDIT_UPD_tblViolation;
/

-- End of DDL Script for Table ISPDEV.TBLVIOLATION

-- Foreign Key
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT fk_violation_officer FOREIGN KEY (iofficerhistoricid)
REFERENCES ISPDEV.tbllofficer (iofficerhistoricid)
DISABLE NOVALIDATE
/
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT fk_violation_location FOREIGN KEY (ilocationhistoricid)
REFERENCES ISPDEV.tbllocation (ilocationhistoricid)
DISABLE NOVALIDATE
/
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT fk_violation_jurisdiction FOREIGN KEY (ijurisdictionhistoricid)
REFERENCES ISPDEV.tbljurisdiction (ijurisdictionhistoricid)
DISABLE NOVALIDATE
/
ALTER TABLE ispdev.tblviolation
ADD CONSTRAINT fk_violation_court FOREIGN KEY (icourtid)
REFERENCES ISPDEV.tblcourt (icourtid)
DISABLE NOVALIDATE
/
-- End of DDL script for Foreign Key(s)
-- Start of DDL Script for Table ISPDEV.TBLVIOLATIONDETAIL
-- Generated 22-Apr-2009 15:31:42 from ISPDEV@photop

CREATE TABLE ispdev.tblviolationdetail
(iviolationdetailid          NUMBER NOT NULL,
ccitationnumber              VARCHAR2(10),
cseatbeltdriverpassenger     CHAR(1),
calcoholurinetestindicator   CHAR(1),
calcoholbreathtestindicator  CHAR(1),
calcoholbloodtestindicator   CHAR(1),
cbreathtestresults           CHAR(2),
cilcsindicator                CHAR(1),
csearchconductedindicator    CHAR(1),
ccontrabandfoundindicator    CHAR(1),
dupdateddate                 DATE,
iupdatedby                    NUMBER,
ichargestatutecitytype       NUMBER,
vcoffensecodenumber          VARCHAR2(7) DEFAULT 116051,
vcoffensesection             VARCHAR2(25),
cbloodalcoholcontent         CHAR(2),
cvehiclesearchtype           CHAR(1),
cpassenger1searchtype        CHAR(1),
cpassenger2searchtype        CHAR(1),
cpassenger3searchtype        CHAR(1),
cpassenger4searchtype        CHAR(1),
cpassenger5searchtype        CHAR(1),
cpassenger6searchtype        CHAR(1),
cdriversearchtype            CHAR(1),
cprimaryreasonforsearch      CHAR(1))
PCTFREE          10
INITRANS         1
MAXTRANS         255

```

```
TABLESPACE ispdev_data
STORAGE (
  INITIAL      1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
```

```
-- Constraints for ISPDEV.TBLVIOLATIONDETAIL
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT pk_violationdetailid PRIMARY KEY (iviolationdetailid)
USING INDEX
  PCTFREE      10
  INITRANS     2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE (
    INITIAL      262144
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_vehsearchtype CHECK (CVEHICLESEARCHTYPE in (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass1searchtype CHECK (CPASSENGER1SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass4searchtype CHECK (CPASSENGER4SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass5searchtype CHECK (CPASSENGER5SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass6searchtype CHECK (CPASSENGER6SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass2searchtype CHECK (CPASSENGER2SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_pass3searchtype CHECK (CPASSENGER3SEARCHTYPE IN (1,2,3,4,5))
```

```
ALTER TABLE ispdev.tblviolationdetail
```

Photo Radar Schema ISPDEV_ddl.sql

```
ADD CONSTRAINT chk_violdetl_driversearchtype CHECK (CDRIVERSEARCHTYPE IN
(1,2,3,4,5))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_violdetl_prisearchreason CHECK (CPRIMARYREASONFORSEARCH IN
(1,2,3,4))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_alcurntestind CHECK (CALCOHOLURINETESTINDICATOR IN ('Y', 'N',
'R'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_alcbreadthtestind CHECK (CALCOHOLBREATHTESTINDICATOR IN ('Y',
'N', 'R'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_alcbloodtestind CHECK (CALCOHOLBLOODTESTINDICATOR IN ('Y', 'N',
'R'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_bloodalcoholcontent CHECK (CBLOODALCOHOLCONTENT IN ('##', '95',
'96', '97', '99'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_ilcsindicator CHECK (CILCSINDICATOR IN ('3', '4'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_searchindicator CHECK (CSEARCHCONDUCTEDINDICATOR IN ('Y', 'N'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_contrabandindicator CHECK (CONTRABANDFOUNDINDICATOR IN ('Y',
'N'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_vehicsearchtype CHECK (CVEHICLESEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_pass1searchtype CHECK (CPASSENGER1SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_pass2searchtype CHECK (CPASSENGER2SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_pass3searchtype CHECK (CPASSENGER3SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
```

Photo Radar Schema ISPDEV_ddl.sql

```

ADD CONSTRAINT chk_pass4searchtype CHECK (CPASSENGER4SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_pass5searchtype CHECK (CPASSENGER5SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_pass6searchtype CHECK (CPASSENGER6SEARCHTYPE IN ('1', '2', '3',
'4', '5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_driversearchtype CHECK (CDRIVERSEARCHTYPE IN ('1', '2', '3', '4',
'5'))
/

ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT chk_reasonforsearch CHECK (CPRIMARYREASONFORSEARCH IN ('1', '2', '3',
'4'))
/

-- End of DDL Script for Table ISPDEV.TBLVIOLATIONDETAIL

-- Foreign Key
ALTER TABLE ispdev.tblviolationdetail
ADD CONSTRAINT fk_violdtl_chgstatutecitttype FOREIGN KEY (ichargestatutecitttype)
REFERENCES ISPDEV.tblchargestatutecitationtypes (ichargestatutecitationtypeid)
/
-- End of DDL script for Foreign Key(s)
-- Start of DDL Script for Table ISPDEV.TBLVIOLATIONLOCATION
-- Generated 22-Apr-2009 15:31:42 from ISPDEV@photop

CREATE TABLE ispdev.tblviolationlocation
(iviolationlocationid          NUMBER NOT NULL,
ccitationnumber                VARCHAR2(10),
vclocationofincident1         VARCHAR2(35),
vclocationofincident2         VARCHAR2(35),
clocationdistancetype         CHAR(2),
vclocationdistance            VARCHAR2(5),
vcmilepostnumber              VARCHAR2(3),
itenths                        NUMBER,
clocationintersectionflag     CHAR(1),
clocationdirection            CHAR(1),
cintersectinghighwaytype      CHAR(1),
dupdateddate                  DATE,
iupdatedby                     NUMBER,
vclatitude                     VARCHAR2(8),
vclongitude                    VARCHAR2(8))
PCTFREE          10
INITRANS         1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE (
  INITIAL        1048576
  MINEXTENTS     1
  MAXEXTENTS     2147483645
)
/

```

Photo Radar Schema ISPDEV_ddl.sql

-- Constraints for ISPDEV.TBLVIOLATIONLOCATION

```
ALTER TABLE ispdev.tblviolationlocation
ADD CONSTRAINT pk_violationlocationid PRIMARY KEY (iviolationlocationid)
USING INDEX
```

```
  PCTFREE      10
  INITTRANS    2
  MAXTRANS     255
  TABLESPACE  ispdev_index
  STORAGE      (
    INITIAL     262144
    MINEXTENTS  1
    MAXEXTENTS  2147483645
  )
/
```

```
ALTER TABLE ispdev.tblviolationlocation
ADD CONSTRAINT chk_vclocation1 CHECK (VCLOCATIONNOFINCIDENT1 IN ('I', 'U', 'S', 'M',
'C', 'R'))
/
```

```
ALTER TABLE ispdev.tblviolationlocation
ADD CONSTRAINT chk_locdisttype CHECK (CLOCATIONDISTANCETYPE IN ('FT', 'MI', ''))
/
```

-- End of DDL Script for Table ISPDEV.TBLVIOLATIONLOCATION

-- Start of DDL Script for Table ISPDEV.TBLXREFUSERROLES
-- Generated 22-Apr-2009 15:31:42 from ISPDEV@photop

```
CREATE TABLE ispdev.tblxrefuserroles
(iuserroleid          NUMBER NOT NULL,
 iroleid              NUMBER,
 iuserid              NUMBER,
 dupdateddate         DATE,
 iupdatedby           NUMBER)
PCTFREE      10
INITTRANS    1
MAXTRANS     255
TABLESPACE   ispdev_data
STORAGE      (
  INITIAL     1048576
  MINEXTENTS  1
  MAXEXTENTS  2147483645
)
/
```

-- Constraints for ISPDEV.TBLXREFUSERROLES

```
ALTER TABLE ispdev.tblxrefuserroles
ADD CONSTRAINT pk_xrefuserroleid PRIMARY KEY (iuserroleid)
USING INDEX
  PCTFREE      10
```

```
INITTRANS      2
MAXTRANS       255
TABLESPACE     ispdev_index
STORAGE        (
  INITIAL       65536
  MINEXTENTS   1
  MAXEXTENTS   2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLXREFUSERROLES

-- Start of DDL Script for Table ISPDEV.TBLYESNO
-- Generated 22-Apr-2009 15:31:42 from ISPDEV@photop

```
CREATE TABLE ispdev.tblyesno
  (iyesnoid          NUMBER NOT NULL,
   vcdescription     VARCHAR2(50))
PCTFREE          10
INITTRANS        1
MAXTRANS         255
TABLESPACE       ispdev_data
STORAGE          (
  INITIAL          1048576
  MINEXTENTS      1
  MAXEXTENTS      2147483645
)
/
```

-- Constraints for ISPDEV.TBLYESNO

```
ALTER TABLE ispdev.tblyesno
ADD CONSTRAINT pk_yesnoid PRIMARY KEY (iyesnoid)
USING INDEX
PCTFREE          10
INITTRANS        2
MAXTRANS         255
TABLESPACE       ispdev_index
STORAGE          (
  INITIAL          65536
  MINEXTENTS      1
  MAXEXTENTS      2147483645
)
/
```

-- End of DDL Script for Table ISPDEV.TBLYESNO